

02-07-00

1

UNITED STATES CONTINUING UTILITY PATENT APPLICATION

under 37 C.F.R. § 1.53(b)

EL171183738US

Atty. Docket No. 03848-85586

CERTIFICATE OF EXPRESS MAILING UNDER 37 C.F.R. § 1.10: The undersigned hereby certifies that this United States Patent Application and all papers noted herein as being attached, are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" Service under 37 C.F.R. § 1.10 today, **February 4, 2000**, and is addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231.

By

*Dena Cuthbert*  
Express Mail Label No.: EL171183738US

JC530 U.S. PTO  
09/498554  
02/04/00

Assistant Commissioner for Patents  
Box Patent Application  
Washington, D.C. 20231

Enclosed herewith is a continuing patent application and the following papers:

Inventors (or application identifier): **James L. Winkler, Stephen P.A. Fodor,  
Christopher J. Buchko, Debra A. Ross,  
Lois Aldwin, and Douglas N. Modlin**

Title of Invention: **COMBINATORIAL STRATEGIES FOR POLYMER SYNTHESIS**

- ☒ Continuation  
☐ Divisional  
☐ Continuation-in-Part

of prior application No. 09/129,463, filed August 4, 1998; which in turn is a continuation of 08/426,202, filed April 21, 1995; which in turn is a continuation of 07/980,523, filed November 20, 1992, now U.S. Patent No. 5,677,195; which in turn is a continuation-in-part of 07/796,243, filed November 22, 1991, now U.S. Patent No. 5,384,261; which in turn is a continuation-in-part of 07/874,849, filed April 24, 1992, now U.S. Patent No. 5,412,087.

1. ☒ Specification 56 pages (including specification, claims, abstract)  
47 claims (7 independent) before recalculation of claims canceled in the enclosed Preliminary Amendment.
2. ☒ Declaration/Power of Attorney:
  - ☒ Copy from Prior Application (for continuation or divisional application)
  - ☐ Newly Executed Declaration (for CIP application)
  - ☐ Deferred under 37 C.F.R. § 1.53(f)
  - ☐ Deletion of Inventor(s) - Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b)

# UNITED STATES CONTINUING UTILITY PATENT APPLICATION

under 37 C.F.R. § 1.53(b)

Page 2

Atty. Docket No. 03848-85586

3. ☒ 21 Distinct sheets of ☒ Formal ☐ Informal Drawings
4. ☒ Preliminary Amendment
5. ☐ Information Disclosure Statement  
☐ Form 1449  
☐ A copy of each cited prior art reference
6. ☒ Assignment  
☐ Assignment with Cover Sheet attached  
☒ Assignment filed in prior application. Application assigned to: **Affymetrix, Inc.**, Santa Clara, California

7. ☐ Priority is hereby claimed under 35 U.S.C. § 119 based upon the following application(s):

Country	Application Number	Date of Filing (day, month, year)

8. ☐ Priority document(s)
9. ☐ Small Entity Statement  
☐ Small Entity Statement was filed in prior application, Small Entity Status is still proper and desired  
☐ is attached  
☐ is no longer claimed
10. ☐ Microfiche Computer Program (Appendix)
11. ☐ Nucleotide and/or Amino Acid Sequence Submission  
☐ Computer Readable Copy  
☐ Paper Copy (identical to computer copy)  
☐ Statement verifying identity of above copies

**UNITED STATES CONTINUING UTILITY PATENT APPLICATION**  
under 37 C.F.R. § 1.53(b)

Page 3

Atty. Docket No. 03848-85586

12. Calculation of Fees after entry of Preliminary Amendment:

FEES FOR	EXCESS CLAIMS	FEE	AMOUNT DUE
Basic Filing Fee (37 C.F.R. § 1.16(a))			\$690.00
Total Claims in Excess of 20 (37 C.F.R. § 1.16(c))	0	18.00	\$0.00
Independent Claims in Excess of 3 (37 C.F.R. § 1.16(b))	0	78.00	\$0.00
Multiple Dependent Claims (37 C.F.R. § 1.16(d))	0	260.00	\$0.00
Subtotal - Filing Fee Due			\$0.00
	MULTIPLY BY		
Reduction by 50%, if Small Entity (37 C.F.R. §§ 1.9, 1.27, 1.28)	0		\$0.00
<b>TOTAL FILING FEE DUE</b>			\$0.00
Assignment Recordation Fee (if applicable) (37 C.F.R. § 1.21(h))	0	40.00	\$0.00
<b>GRAND TOTAL DUE</b>			<b>\$690.00</b>

13. PAYMENT is:


- ☒ included in the amount of the GRAND TOTAL. The commissioner is hereby authorized to charge the filing fee of \$690.00 to Deposit Account No. 19-0733. A general authorization under 37 C.F.R. § 1.25(b), second sentence, is hereby given to credit or debit our Deposit Account No. 19-0733 for the instant filing and for any other fees during the pendency of this application under 37 C.F.R. §§ 1.16, 1.17 and 1.18
- ☐ not included, but deferred under 37 C.F.R. § 1.53(f).

14. All correspondence for the attached application should be directed to:

John P. Iwanicki  
Banner & Witcoff, Ltd.  
28 State Street, 28th Floor  
Boston, MA 02109  
Telephone: (617) 227-7111  
Facsimile: (617) 227-4399

15. Other: \_\_\_\_\_

Date: February 4, 2000

By:   
John P. Iwanicki  
Reg. No. 34,628

JPI/lh

Enclosures

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re Application of:	)	
	)	
James L. Winkler, Stephen P.A. Fodor,	)	Examiner:
Christopher J. Buchko, Debra A. Ross,	)	
Lois Aldwin, and Douglas N. Modlin	)	Art Unit:
	)	
Serial No.: TBA	)	
	)	
Filed: Herewith	)	
	)	
Title: COMBINATORIAL STRATEGIES	)	
FOR POLYMER SYNTHESIS	)	

Assistant Commissioner for Patents  
Box Patent Application  
Washington, D.C. 20231

**PRELIMINARY AMENDMENT**

This amendment is being filed with the continuation application. Preliminary to examination, please amend the above-referenced patent application as follows:

In the specification:

At page 1, before paragraph 1 insert the following:

--This application is a continuation of U.S. Patent Application No. 09/129,463, filed August 4, 1998; which in turn is a continuation of U.S. Patent Application No. 08/426,202, filed April 21, 1995; which in turn is a continuation of U.S. Patent Application No. 07/980,523, filed November 20, 1992, now U.S. Patent No. 5,677,195; which in turn is a continuation-in-part of U.S. Patent Application

No. 07/796,243, filed November 22, 1991, now U.S. Patent No. 5,384, 261; which in turn is a continuation-in-part of U.S. Patent Application No. 07/874,849, filed April 24, 1992, now U.S. Patent No. 5,412,087.--

In the claims:

Please cancel claims 2 through 47 without prejudice to the filing of any appropriate continuation application.

REMARKS

Prior to the calculation of the filing fee, applicants respectfully request entry of the above amendments.

Respectfully submitted,

Dated: February 4, 2000



John P. Iwanicki, Reg. No. 34,628  
BANNER & WITCOFF, LTD.  
28 State Street, 28th Floor  
Boston, MA 02109  
(617) 227-7111

## PATENT APPLICATION

### COMBINATORIAL STRATEGIES FOR POLYMER SYNTHESIS

#### Inventor(s):

JAMES L. WINKLER, a citizen of the United States of America, residing in Palo Alto, California;

STEPHEN P.A. FODOR, a citizen of the United States of America, residing in Palo Alto, California;

CHRISTOPHER J. BUCHKO, a citizen of the United States of America, residing in Ann Arbor, Michigan;

DEBRA A. ROSS, a citizen of the United States of America, residing in Fremont, California;

LOIS ALDWIN, a citizen of the United States of America, residing in San Mateo county, California; and

DOUGLAS N. MODLIN, a citizen of the United States, residing in Palo Alto, California.

#### Assignee:

AFFYMAX TECHNOLOGIES N.V.  
De Ruyderkade 62  
Curacao, NETHERLANDS ANTILLES

(a Netherlands Antilles corporation)

TOWNSEND and TOWNSEND  
Steuart Street Tower  
One Market Plaza  
San Francisco, CA 94105  
(415) 326-2400

COMBINATORIAL STRATEGIES FOR POLYMER SYNTHESIS

## BACKGROUND OF THE INVENTION

5 This application is a continuation-in-part of U.S. Serial No. 796,243 (filed November 22, 1991) which is incorporated herein by reference for all purposes. This application is also a continuation-in-part of U.S. Serial No. 874,849 (filed April 24, 1992), which is incorporated herein by reference for all purposes.

10 The present invention relates to the field of polymer synthesis and screening. More specifically, in one embodiment the invention provides an improved method and system for synthesizing arrays of diverse polymer sequences. According to a specific aspect of the invention, a method of synthesizing diverse polymer sequences  
15 such as peptides or oligonucleotides is provided. The diverse polymer sequences may be used, for example, in screening studies for determination of binding affinity.

Methods of synthesizing desired polymer sequences such as peptide sequences are well known to those of skill in the art.  
20 Methods of synthesizing oligonucleotides are found in, for example, Oligonucleotide Synthesis: A Practical Approach, Gate, ed., IRL Press, Oxford (1984), incorporated herein by reference in its entirety for all purposes. The so-called "Merrifield" solid phase peptide synthesis has been in common use for several years and is  
25 described in Merrifield, J. Am. Chem. Soc. (1963) 85:2149-2154, incorporated herein by reference for all purposes. Solid-phase synthesis techniques have been provided for the synthesis of several peptide sequences on, for example, a number of "pins." See e.g., Geysen et al., J. Immun. Meth. (1987) 102:259-274, incorporated  
30 herein by reference for all purposes. Other solid-phase techniques involve, for example, synthesis of various peptide sequences on different cellulose disks supported in a column. See Frank and Doring, Tetrahedron (1988) 44:6031-6040, incorporated herein by reference for all purposes. Still other solid-phase techniques are  
35 described in U.S. Patent No. 4,728,502 issued to Hamill and WO 90/00626 (Beattie, inventor).

Each of the above techniques produces only a relatively low density array of polymers. For example, the technique described in Geysen et al. is limited to producing 96 different polymers on  
40 pins spaced in the dimensions of a standard microtiter plate.

Improved methods of forming large arrays of peptides, oligonucleotides, and other polymer sequences in a short period of time have been devised. Of particular note, Pirrung et al., U.S. Patent No. 5,143,854 (see also PCT Application No. WO 90/15070) and  
45 Fodor et al., PCT Publication No. WO 92/10092, all incorporated herein by reference, disclose methods of forming vast arrays of

The VLSIPS™ techniques have met with substantial success. However, in some cases it is desirable to have alternate/additional methods of forming polymer sequences which would not utilize, for example, light as an activator, or which would not utilize light exclusively.

Methods and devices for synthesizing high-density arrays of diverse polymer sequences such as diverse peptides and oligonucleotides are provided by virtue of the present invention. In addition, methods and devices for delivering (and, in some cases, immobilizing) available libraries of compounds on specific regions of a substrate are provided by this invention. In preferred embodiments, various monomers or other reactants are delivered to multiple reaction sites on a single substrate where they are reacted in parallel.

According to the first specific aspect of the invention, a block having a series of channels, such as grooves, on a surface thereof is utilized. The block is placed in contact with a derivatized glass or other substrate. In a first step, a pipettor or other delivery system is used to flow selected reagents to one or more of a



series of apertures connected to the channels, or place reagents in the channels directly, filling the channels and "striping" the substrate with a first reagent, coupling a first group of monomers thereto. The first group of monomers need not be homogenous. For example, a monomer A may be placed in a first group of the channels, a monomer B in a second group of channels, and a monomer C in a third group of channels. The channels may in some embodiments thereafter be provided with additional reagents, providing coupling of additional monomers to the first group of monomers. The block is then translated or rotated, again placed on the substrate, and the process is repeated with a second reagent, coupling a second group of monomers to different regions of the substrate. The process is repeated until a diverse set of polymers of desired sequence and length is formed on the substrate. By virtue of the process, a number of polymers having diverse monomer sequences such as peptides or oligonucleotides are formed on the substrate at known locations.

According to the second aspect of the invention, a series of microchannels or microgrooves are formed on a substrate, along with an appropriate array of microvalves. The channels and valves are used to flow selected reagents over a derivatized surface. The microvalves are used to determine which of the channels are opened for any particular coupling step.

Accordingly, one embodiment of the invention provides a method of forming diverse polymer sequences on a single substrate, the substrate comprising a surface with a plurality of selected regions. The method includes the steps of forming a plurality of channels adjacent the surface, the channels at least partially having a wall thereof defined by a portion of the selected regions; and placing selected reagents in the channels to synthesize polymer sequences at the portion of the selected regions, the portion of the selected regions comprising polymers with a sequence of monomers different from polymers in at least one other of the selected regions. In alternative embodiments, the channels or flow paths themselves constitute the selected reaction regions. For example, the substrate may be a series of adjoining parallel channels, each having reaction sites therein.

According to a third aspect of the invention, a substrate is provided which has an array of discrete reaction regions separated from one another by inert regions. In one embodiment, a first monomer solution is spotted on a first set of reaction regions of a suitably derivatized substrate. Thereafter, a second monomer solution is spotted on a second set of regions, a third monomer solution is spotted on a third set and so on, until a number of the regions each have one species of monomer located therein. These monomers are reacted with the surface, and the substrate is

subsequently washed and prepared for reaction with a new set of monomers. Dimers, trimers, and larger polymers of controlled length and monomer sequence are prepared by repeating the above steps with different groupings of the reaction regions and monomer solutions.

- 5 In alternative embodiments, the polymers or other compounds of the array are delivered to the regions as complete species, and thus the above polymer synthesis steps are unnecessary.

In a preferred embodiment, a plurality of reaction regions on the substrate surface are surrounded by a constraining region such as a non-wetting region which hinders the transport of reactants between adjacent reaction regions. Thus, the reactants in one region cannot flow to other regions where they could contaminate the reaction. In certain preferred embodiments, the regions of the array are defined by selective irradiation of a substrate surface containing photolabile hydrophobic protecting groups. In areas where the surface is irradiated, the hydrophobic protecting groups are removed to define reaction regions. When an aqueous or other polar reactant solution is deposited in the reaction region, it will have a relatively large wetting angle with the substrate surface so that by adjusting the amount deposited, one can ensure no flow to adjacent regions.

A further understanding of the nature and advantages of the inventions herein may be realized by reference to the remaining portions of the specification and the attached drawings.

25

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a generalized diagram illustrating the invention;

Fig. 2 is a flow chart illustrating the treatment steps performed in synthesizing an array of various polymers;

Fig. 3 is a mapping of a resulting array of polymers;

Fig. 4a to 4c illustrate the arrangement of three channel block templates in six process steps employed to synthesize 64 million hexapeptides from a 20 amino acid basis set;

Fig. 5a is a top view and Fig. 5b is a cross-sectional view of a first embodiment of a device used to synthesize arrays of polymer sequences;

Fig. 6 is a cross-sectional view of an embodiment containing a pressure chamber for holding a substrate against a channel block;

Figs. 7a and 7b are top views of two of two different "fanned array" channel blocks;

Fig. 8 is a cross-sectional view of a channel block and associated flow ports according to one embodiment of the invention;

Fig. 9 is a detailed cross-sectional view of the flow ports in a channel block;

Fig. 10 is a diagram of a flow system used to deliver coupling compounds and reagents to a flow cell;

5 Figs. 11a and 11b show an apparatus used to transfer a substrate from one channel block to another;

Fig. 12 is a diagram of a multichannel solid-phase synthesizer;

10 Figs. 13a and 13b illustrate alternative arrangements of the grooves in a channel block;

Fig. 14 is a schematic illustration of reaction pathways used to prepare some hydrophobic groups of the present invention;

Figs. 15a and 15b illustrate a microvalve device;

15 Figs. 16a and 16b illustrate an alternative embodiment of the invention;

Fig. 17 is a mapping of expected fluorescent intensities with a substrate selectively exposed to fluorescent dye;

Fig. 18 is a mapping of actual fluorescence intensity versus location;

20 Fig. 19 is a mapping of fluorescence intensity versus location on a slide having four different peptides synthesized thereon;

Fig. 20 is a mapping of fluorescence intensity versus location indicating fluorescein binding on 400 micron wide photolyzed regions perpendicular to 100 micron flow paths;

25 Fig. 21 is a mapping of fluorescence intensity versus location for a substrate containing octanucleotides, heptanucleotides, and hexanucleotides and incubated with an oligonucleotide complimentary to the octanucleotide; and

30 Fig. 22 is a magnified version of Fig. 21.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

## CONTENTS

	I. Glossary
5	II. General
	III. Methods for Mechanical Delivery of Reagents
	IV. Flow Channel Embodiments
	V. Spotting Embodiments
10	VI. Alternative Embodiments
	VII. Examples
	A. Leak Testing
	B. Formation of YGGFL
	C. 100 Micron Channel Block
15	D. Channel Matrix Hybridization Assay

## VIII. Conclusion

20 I. Glossary

The following terms are intended to have the following general meanings as they are used herein:

- 25 1. Ligand: A ligand is a molecule that is recognized by a receptor. Examples of ligands that can be investigated by this invention include, but are not restricted to, agonists and antagonists for cell membrane receptors, toxins and venoms, viral epitopes, hormones, opiates, steroids, peptides, enzyme substrates, cofactors, drugs, lectins, sugars,
   
30 oligonucleotides, nucleic acids, oligosaccharides, and proteins.
- 35 2. Monomer: A monomer is a member of the set of small molecules which are or can be joined together to form a polymer or a compound composed of two or more members. The set of monomers includes but is not restricted to, for example, the set of common L-amino acids, the set of D-amino acids, the set of synthetic and/or natural amino acids, the set of nucleotides and the set of pentoses and hexoses. The particular ordering
   
40 of monomers within a polymer is referred to herein as the "sequence" of the polymer. As used herein, monomers refers to any member of a basis set for synthesis of a polymer. For example, dimers of the 20 naturally occurring L-amino acids form a basis set of 400 monomers for synthesis of polypeptides.
   
45 Different basis sets of monomers may be used at successive

steps in the synthesis of a polymer. Furthermore, each of the sets may include protected members which are modified after synthesis. The invention is described herein primarily with regard to the preparation of molecules containing sequences of monomers such as amino acids, but could readily be applied in the preparation of other polymers. Such polymers include, for example, both linear and cyclic polymers of nucleic acids, polysaccharides, phospholipids, and peptides having either  $\alpha$ -,  $\beta$ -, or  $\omega$ -amino acids, heteropolymers in which a known drug is covalently bound to any of the above, polynucleotides, polyurethanes, polyesters, polycarbonates, polyureas, polyamides, polyethyleneimines, polyarylene sulfides, polysiloxanes, polyimides, polyacetates, or other polymers which will be apparent upon review of this disclosure. Such polymers are "diverse" when polymers having different monomer sequences are formed at different predefined regions of a substrate. Methods of cyclization and polymer reversal of polymers are disclosed in copending application Serial No. 796,727, filed November 22, 1991, entitled "POLYMER REVERSAL ON SOLID SURFACES," incorporated herein by reference for all purposes.

3. Peptide: A peptide is a polymer in which the monomers are alpha amino acids and are joined together through amide bonds, alternatively referred to as a polypeptide. Amino acids may be the L-optical isomer or the D-optical isomer. Peptides are two or more amino acid monomers long and are often more than 20 amino acid monomers long. Standard abbreviations for amino acids are used (e.g., P for proline). These abbreviations are included in Stryer, Biochemistry, Third Ed., 1988, which is incorporated herein by reference for all purposes.

4. Receptor: A receptor is a molecule that has an affinity for a ligand. Receptors may be naturally-occurring or manmade molecules. They can be employed in their unaltered state or as aggregates with other species. Receptors may be attached, covalently or noncovalently, to a binding member, either directly or via a specific binding substance. Examples of receptors which can be employed by this invention include, but are not restricted to, antibodies, cell membrane receptors, monoclonal antibodies and antisera reactive with specific antigenic determinants, viruses, cells, drugs, polynucleotides, nucleic acids, peptides, cofactors, lectins, sugars, polysaccharides, cellular membranes, and organelles. Receptors are sometimes referred to in the art as anti-ligands. As the

term receptors is used herein, no difference in meaning is intended. A "Ligand Receptor Pair" is formed when two molecules have combined through molecular recognition to form a complex.

Specific examples of receptors which can be investigated by this invention include but are not restricted to:

- a) Microorganism receptors: Determination of ligands that bind to microorganism receptors such as specific transport proteins or enzymes essential to survival of microorganisms would be a useful tool for discovering new classes of antibiotics. Of particular value would be antibiotics against opportunistic fungi, protozoa, and bacteria resistant to antibiotics in current use.
- b) Enzymes: For instance, a receptor can comprise a binding site of an enzyme such as an enzyme responsible for cleaving a neurotransmitter; determination of ligands for this type of receptor to modulate the action of an enzyme that cleaves a neurotransmitter is useful in developing drugs that can be used in the treatment of disorders of neurotransmission.
- c) Antibodies: For instance, the invention may be useful in investigating a receptor that comprises a ligand-binding site on an antibody molecule which combines with an epitope of an antigen of interest; determining a sequence that mimics an antigenic epitope may lead to the development of vaccines in which the immunogen is based on one or more of such sequences or lead to the development of related diagnostic agents or compounds useful in therapeutic treatments such as for autoimmune diseases (e.g., by blocking the binding of the "self" antibodies).
- d) Nucleic Acids: Sequences of nucleic acids may be synthesized to establish DNA or RNA binding sequences that act as receptors for synthesized sequence.
- e) Catalytic Polypeptides: Polymers, preferably antibodies, which are capable of promoting a chemical reaction involving the conversion of one or more reactants to one or more products. Such polypeptides generally include a binding site specific for at least one reactant or reaction intermediate and an active functionality proximate to the binding site, which functionality is capable of chemically modifying the bound reactant. Catalytic polypeptides and others are described in, for example, PCT Publication No. WO 90/05746,

WO 90/05749, and WO 90/05785, which are incorporated herein by reference for all purposes.

- f) Hormone receptors: Determination of the ligands which bind with high affinity to a receptor such as the receptors for insulin and growth hormone is useful in the development of, for example, an oral replacement of the daily injections which diabetics must take to relieve the symptoms of diabetes or a replacement for growth hormone. Other examples of hormone receptors include the vasoconstrictive hormone receptors; determination of ligands for these receptors may lead to the development of drugs to control blood pressure.
  - g) Opiate receptors: Determination of ligands which bind to the opiate receptors in the brain is useful in the development of less-addictive replacements for morphine and related drugs.
5. Substrate: A material having a rigid or semi-rigid surface. In many embodiments, at least one surface of the substrate will be substantially flat, although in some embodiments it may be desirable to physically separate synthesis regions for different polymers with, for example, wells, raised regions, etched trenches, or the like. In some embodiments, the substrate itself contains wells, trenches, flow through regions, etc. which form all or part of the synthesis regions. According to other embodiments, small beads may be provided on the surface, and compounds synthesized thereon may be released upon completion of the synthesis.
  6. Channel Block: A material having a plurality of grooves or recessed regions on a surface thereof. The grooves or recessed regions may take on a variety of geometric configurations, including but not limited to stripes, circles, serpentine paths, or the like. Channel blocks may be prepared in a variety of manners, including etching silicon blocks, molding or pressing polymers, etc.
  7. Protecting Group: A material which is bound to a monomer unit and which may be selectively removed therefrom to expose an active site such as, in the specific example of an amino acid, an amine group. Specific examples of photolabile protecting groups are discussed in Fodor et al., PCT Publication No. WO 92/10092 (previously incorporated by reference) and U.S. Serial No. \_\_\_\_\_ filed November 2, 1992 (attorney docket No. 11509-68) incorporated herein by reference for all purposes.

8. Predefined Region: A predefined region is a localized area on a substrate which is, was, or is intended to be used for formation of a selected polymer and is otherwise referred to herein in the alternative as "reaction" region, a "selected" region, or simply a "region." The predefined region may have any convenient shape, e.g., circular, rectangular, elliptical, wedge-shaped, etc. In some embodiments, a predefined region and, therefore, the area upon which each distinct polymer sequence is synthesized is smaller than about 1 cm<sup>2</sup>, more preferably less than 1 mm<sup>2</sup>, and still more preferably less than 0.5 mm<sup>2</sup>. In most preferred embodiments the regions have an area less than about 10,000 μm<sup>2</sup> or, more preferably, less than 100 μm<sup>2</sup>. Within these regions, the polymer synthesized therein is preferably synthesized in a substantially pure form.
9. Substantially Pure: A polymer is considered to be "substantially pure" within a predefined region of a substrate when it exhibits characteristics that distinguish it from other predefined regions. Typically, purity will be measured in terms of biological activity or function as a result of uniform sequence. Such characteristics will typically be measured by way of binding with a selected ligand or receptor. Preferably the region is sufficiently pure such that the predominant species in the predefined region is the desired sequence. According to preferred aspects of the invention, the polymer is at least 5% pure, more preferably more than 10% to 20% pure, more preferably more than 80% to 90% pure, and most preferably more than 95% pure, where purity for this purpose refers to the ratio of the number of ligand molecules formed in a predefined region having a desired sequence to the total number of molecules formed in the predefined region.

## II. General

The invention can be used in variety of applications. For example, the invention can be used as a synthesis tool (as for example in peptide syntheses), as a screening tool (as for example in screening compound libraries for drug activity), or as a monitoring/diagnostic tool (as for example in medical or environmental testing). In one specific embodiment, the invention is used for nucleic acid-based diagnostics.

As a synthesis tool, the present invention provides for the formation of arrays of large numbers of different polymer sequences. According to a preferred embodiment, the invention provides for the synthesis of an array of different peptides or



oligonucleotides in selected regions of a substrate. Such substrates having the diverse sequences formed thereon may be used in, for example, screening studies to evaluate their interaction with receptors such as antibodies and nucleic acids. For example, in preferred embodiments the invention provides for screening of peptides to determine which if any of a diverse set of peptides has a strong binding affinity with a receptor and, in most preferred embodiments, to determine the relative binding affinity of various peptides with a receptor of interest.

Such diverse polymer sequences are preferably synthesized on a single substrate. By synthesizing the diverse polymer sequences on a single substrate, processing of the sequences to evaluate characteristics such as relative binding affinity is more easily conducted. By way of example, when an array of peptide sequences (or a library of other compounds) is to be evaluated to determine the peptides' relative binding affinity to a receptor, the entire substrate and, therefore, all or a group of the polymer sequences may be exposed to an appropriately labelled receptor and evaluated simultaneously.

In some embodiments, the present invention can be employed to localize and, in some cases, immobilize vast collections of synthetic chemical compounds or natural product extracts. In such methods, compounds are deposited on predefined regions of a substrate. The reaction of the immobilized compound (or compounds) with various test compositions such as the members of the chemical library or a biological extract are tested by dispensing small aliquots of each member of the library or extract to a different region. Competitive assays or other well-known techniques can be used to identify a desired activity. As an example, a large collection of human receptors is deposited on a substrate, one in each region to form an array. A plant/animal extract is then screened for binding to various receptors of the array.

The present invention has certain features in common with the "light directed" methods described in U.S. Patent No. 5,143,854, previously incorporated by reference. The light directed methods discussed in the '854 patent involve activating predefined regions of the substrate and then contacting the substrate with a preselected monomer solution. The predefined regions can be activated with a light source shown through a mask (much in the manner of photolithography techniques used in integrated circuit fabrication). Other regions of the substrate remain inactive because they are blocked by the mask from illumination. Thus, a light pattern defines which regions of the substrate react with a given monomer. By repeatedly activating different sets of predefined regions and contacting different monomer solutions with the substrate, a diverse

array of polymers is produced on the substrate. Of course, other steps such as washing unreacted monomer solution from the substrate can be used as necessary.

In the present invention, a mechanical device or physical structure defines the regions which are available to react with a given monomer. In some embodiments, a wall or other physical barrier is used to block a given monomer solution from contacting any but a few selected regions of a substrate. In other embodiments, the amount of the monomer (or other) solution deposited and the composition of the substrate act to separate different monomer solutions on the substrate. This permits different monomers to be delivered and coupled to different regions simultaneously (or nearly simultaneously) and reduces the number of separate washing and other reaction steps necessary to form an array of polymers. Further, the reaction conditions at different activated regions can be controlled independently. Thus, the reactant concentrations and other parameters can be varied independently from reaction site to reaction site, to optimize the procedure.

In alternative preferred embodiments of the present invention, light or another activator is used in conjunction with the physical structures to define reaction regions. For example, a light source activates various regions of the substrate at one time and then a mechanical system directs monomer solutions to different activated regions, in parallel.

### III. Methods for Mechanical Delivery of Reagents

In preferred embodiments of the present invention, reagents are delivered to the substrate by either (1) flowing within a channel defined on predefined regions or (2) "spotting" on predefined regions. However, other approaches, as well as combinations of spotting and flowing, may be employed. In each instance, certain activated regions of the substrate are mechanically separated from other regions when the monomer solutions are delivered to the various reaction sites.

A typical "flow channel" method of the present invention can generally be described as follows. Diverse polymer sequences are synthesized at selected regions of a substrate by forming flow channels on a surface of the substrate through which appropriate reagents flow or in which appropriate reagents are placed. For example, assume a monomer "A" is to be bound to the substrate in a first group of selected regions. If necessary, all or part of the surface of the substrate in all or a part of the selected regions is activated for binding by, for example, flowing appropriate reagents through all or some of the channels, or by washing the entire substrate with appropriate reagents. After placement of a channel

block on the surface of the substrate, a reagent having the monomer A flows through or is placed in all or some of the channel(s). The channels provide fluid contact to the first selected regions, thereby binding the monomer A on the substrate directly or indirectly (via a linker) in the first selected regions.

5       Thereafter, a monomer B is coupled to second selected regions, some of which may be included among the first selected regions. The second selected regions will be in fluid contact with a second flow channel(s) through translation, rotation, or replacement  
10       of the channel block on the surface of the substrate; through opening or closing a selected valve; or through deposition of a layer of photoresist. If necessary, a step is performed for activating at least the second regions. Thereafter, the monomer B is flowed  
15       through or placed in the second flow channel(s), binding monomer B at the second selected locations. In this particular example, the resulting sequences bound to the substrate at this stage of processing will be, for example, A, B, and AB. The process is repeated to form a vast array of sequences of desired length at known locations on the substrate.

20       After the substrate is activated, monomer A can be flowed through some of the channels, monomer B can be flowed through other channels, a monomer C can be flowed through still other channels, etc. In this manner, many or all of the reaction regions are reacted with a monomer before the channel block must be moved or the  
25       substrate must be washed and/or reactivated. By making use of many or all of the available reaction regions simultaneously, the number of washing and activation steps can be minimized.

      Various embodiments of the invention will provide for alternative methods of forming channels or otherwise protecting a  
30       portion of the surface of the substrate. For example, according to some embodiments, a protective coating such as a hydrophilic or hydrophobic coating (depending upon the nature of the solvent) is utilized over portions of the substrate to be protected, sometimes in combination with materials that facilitate wetting by the reactant  
35       solution in other regions. In this manner, the flowing solutions are further prevented from passing outside of their designated flow paths.

      The "spotting" embodiments of the present invention can be implemented in much the same manner as the flow channel  
40       embodiments. For example, a monomer A can be delivered to and coupled with a first group of reaction regions which have been appropriately activated. Thereafter, a monomer B can be delivered to and reacted with a second group of activated reaction regions. Unlike the flow channel embodiments described above, reactants are  
45       delivered by directly depositing (rather than flowing) relatively

small quantities of them in selected regions. In some steps, of course, the entire substrate surface can be sprayed or otherwise coated with a solution. In preferred embodiments, a dispenser moves from region to region, depositing only as much monomer as necessary at each stop. Typical dispensers include a micropipette to deliver the monomer solution to the substrate and a robotic system to control the position of the micropipette with respect to the substrate. In other embodiments, the dispenser includes a series of tubes, a manifold, an array of pipettes, or the like so that various reagents can be delivered to the reaction regions simultaneously.

#### IV. Flow Channel Embodiments

Fig. 1 illustrates an example of the invention. In this particular example, monomers and dimers of the monomer group A, B, C, and D are to be bound at selected regions of the substrate. The substrate may be biological, nonbiological, organic, inorganic, or a combination of any of these, existing as particles, strands, precipitates, gels, sheets, tubing, spheres, containers, capillaries, pads, slices, films, plates, slides, etc. The substrate may have any convenient shape, such as a disc, square, sphere, circle, etc. The substrate is preferably flat but may take on a variety of alternative surface configurations. For example, the substrate may contain raised or depressed regions on which the synthesis takes place.

The substrate and its surface form a support on which to carry out the reactions described herein. These monomers are bound using first flow channel paths  $x_1$ ,  $x_2$ ,  $x_3$ , and  $x_4$  which are formed or placed on or adjacent the substrate in a first orientation, and second flow channel paths  $y_1$ ,  $y_2$ ,  $y_3$ , and  $y_4$  which are formed or placed on or adjacent the substrate in a second orientation. The second flow channel paths intersect at least a part of the first flow channel paths. The flow channels are formed according to techniques which are described in greater detail elsewhere herein.

Initially the substrate is subjected to one or more preliminary treatments such as, for example, cleaning and the optional placement of "linker" molecules on the surface thereof. The substrate may also be provided with various active groups, common monomer sequences which will form a part of the polymers, or the like.

Thereafter, in a first coupling step, one or more of the flow channels are provided with the first monomer A, which binds through covalent bonds or otherwise to the substrate (directly or indirectly) where the flow channel contacts the substrate. In the particular example shown in Fig. 1, the flow channels  $x_1$  and  $x_2$  are utilized, binding the monomer A to the substrate along the entire

length of the substrate adjacent to the  $x_1$  and  $x_2$  channels. Each coupling step may in some embodiments be composed of a variety of substeps. For example, each coupling step may include one or more substeps for washing, chemical activation, or the like.

5           Thereafter or concurrently therewith, as shown in Fig. 2, a second monomer B is provided to selected flow channels and the monomer B binds to the substrate where the second flow channels provide contact therewith. In the particular example shown in Fig. 2, monomer B is bound along channels  $x_3$  and  $x_4$ . When the monomers A and B flow through their respective flow channels simultaneously, only a single process step is required to perform two coupling steps simultaneously. As used herein, a "process step" refers to the injection of one or more channels with one or more reagents. A "coupling step" refers to the addition of a monomer in a polymer.

10           Processing thereafter continues in a similar manner with monomers C and D in the manner shown in the flow diagram of Fig. 2, with monomer C being bound in the flow channels  $y_1$  and  $y_2$ , and D being bound in the flow channels  $y_3$  and  $y_4$ . Preferably, monomers C and D are directed through the flow channels  $y_1$  to  $y_4$  simultaneously whereby two coupling steps are performed with a single process step. Light regions in Fig. 1 indicate the intersections of the resulting flow paths.

15           Fig. 3 illustrates the mapping of sequences formed using the above illustrated steps. As shown therein, the sequences A, B, C, D, AD, BD, AC, and BC have been formed using only two process steps. Accordingly, it is seen that the process provides for the synthesis of vast arrays of polymer sequences using only a relatively few process steps. By way of further example, it is necessary to use only two process steps to form all of the  $4^2 = 16$  dimers of a four-monomer basis set. By way of further example, to form all  $4^8$  octomers of a four-monomer basis set, it is necessary to provide only 256 flow channels oriented in the "x" direction, and 256 flow channels oriented in the "y" direction, with a total of eight coupling steps.

20           The power of the technique is further illustrated by synthesizing the complete array of six hexamer peptides from a 20 amino acid basis set. This array will include  $20^6$  or 64,000,000 regions defining 64,000,000 different peptides and can be formed in only six process steps. Further, the method requires only three different templates, one having 20 parallel channels, a second having 400 channels each 1/20th as wide as the first, and a third having 8000 channels each 1/20th as wide as the second. Each template will be used in two process steps, each at an orientation at 90 degrees with respect to the other as illustrated in Fig. 4. With the first

template, the substrate is activated and then solutions of each of the 20 amino acid basis set (or other 20 member basis set) are flowed over and reacted on a different predefined stripe in a first orientation. This is the first process step and includes 20 coupling or attachment steps, which can be performed simultaneously. Next, the entire substrate is again activated and the first template is placed in a second orientation, perpendicular to the first (Fig. 4a). The 20 amino acid solutions are then flowed along 20 new predefined stripes (each perpendicular to the original set of stripes). In each of these two process steps, the 20 predefined regions (the stripes along the flow channels) are first activated and then contacted with the individual monomers so that all 20 stripes are reacted before the next activation step is necessary. In other words, 20 coupling steps are conducted in parallel, greatly reducing the number of necessary activation steps.

The four remaining coupling steps employ the second and third templates. In the third and fourth process steps (Fig. 4b), 20 channels are devoted to each monomer, and in the fifth and sixth process steps (Fig. 4c), 400 channels are devoted to each monomer. As with the first two steps, the entire substrate undergoes reaction during a single process step. Thus, only six process steps (requiring a total of about 24 hours) are required to produce the entire library of 64,000,000 peptide hexamers. In a different embodiment, a single template having 8000 channels to control delivery (e.g. 400 channels for each of the 20 amino acids in the first round) can produce the full library of hexamers with only a single rotation step. Thus, the present invention offers extremely rapid methods of preparing diverse polymer arrays.

Figs. 5a and 5b illustrate details of a first embodiment of a device used for performing the synthesis steps described above. In particular, Fig. 5a illustrates the device in top view, while Fig. 5b illustrates the device in cross-sectional side view. In the particular embodiment shown in Fig. 5, the device is used to synthesize polymer sequences on substrate 401. Substrate 401 is coupled to a rotating stage 403 and removably held by clamp 405 to channel block 407. Channel block 407 has etched therein a plurality of channels 409 in the form of stripes therein. Each channel is provided with a flow inlet 411 and an outlet 413. A vacuum source 415 is applied to one or more of the outlets 413, while a pipettor 417 is slidably mounted on arm 419 to deliver selected reagents from reservoir(s) 421 to selected flow inlets 411.

The details of a second preferred embodiment are shown in Figs. 6-11. Fig. 6 displays an apparatus for holding a substrate 111 in place against a channel block 109 by evenly distributing pressure over the substrate in a pressure chamber 101. Pressurized gas is

admitted through gas pressure inlet 103 to provide clamping pressure to immobilize the substrate while fluids are flowed from fluid flow inlet 115, through channel 123, and out fluid outlet 117. The upper and lower portions of the pressure chamber housing 105 and 125 are held together by nuts 121 and bolts 104. Of course, other means such as clamps can be used to hold the pressure chamber housing portions together.

Fig. 7 illustrates preferred flow path configurations in channel blocks of the present invention. As shown in Figs. 7a, fluid delivery sites 127, 129, 131, 133, 135, and 137 are connected to channels leading to reaction region 141. A similar arrangement is shown for comparison in Fig. 7b where the orientation of the flow channels in the reaction regions is shifted by 90 degrees on a rectangular channel block. Vacuum ports 145 and 146 to an external vacuum line are provided so that substrate position is maintained during fluid flow.

The channels shown in Figs. 7a and 7b form a "fanned channel array" on channel block 139 in a manner analogous to that of the lead pattern employed in integrated circuits. This provides significantly increased separation of fluid delivery points in comparison to the high density of channels in the reaction region. In a 2 inch by 3 inch substrate, at least about a 4:1 increase in spatial separation typically can be attained by the fanned arrangement. Thus, if the channels in the reaction regions are separated by 200 microns, the delivery ports can be separated by 0.8 mm.

The spatial separation can be further increased by staggering the delivery ports as shown for ports 127, 129, and 131. This can provide an additional channel separation of at least about 3:1. Thus, for the channels separated by 200 microns, a staggered fanned array provides 2.4 mm separation between the delivery ports. Thus, fluid can be delivered to a high-density array of channels in the reaction region from standard 1.6 mm Teflon™ tubing. If additional spacing is necessary, the substrate size can be increased, while preserving the reaction region size.

As shown in Fig. 8, the fluid delivery ports are accessed from holes in the back surface of a stabilizing plate 108 on the channel block. The stabilizing plate, which is preferably made from fused pyrex, provides structural integrity to the channel block during clamping in the pressure chamber. It may also provide a means to access the channel block ports and reduce leakage between ports or channels. In preferred embodiments, the channels 123 of the channel block are formed on a wafer 106 which generally may be any machinable or cast material, and preferably may be etched silicon or a micromachined ceramic. In other embodiments, the channel block is

pressure-formed or injection-molded from a suitable polymer material. The entire channel block arrangement is mounted on a rigid channel block sub-plate 110 including a vacuum line 112, ports for fluid delivery lines 115, ports for fluid outlet lines 117, and recessed regions for plug ends 151 and 153. With this arrangement, the substrate can be clamped against the top surface of the channel block (by vacuum or pressurized gas as shown in the embodiment of Fig. 6) while fluid enters and exits from below. Preferably, the subplate will be made from a rigid material such as stainless steel or anodized aluminum.

Individual micro tubing connections can be made for each channel as shown in Fig. 9. Plug ends 151 are provided with a conical upper surface that mates with a conical recess 118 in pyrex stabilizing plate 108. Plug ends 151 also have a cylindrical lower surface that mates with cylindrical recess 116 in sub-plate 110. The subplate and stabilizing plate are held together by bolt 114 and threaded insert 112 or other suitable engagement means.

Fig. 10 shows a fluid flow diagram of a preferred system of the present invention. The pressure is controlled at point 25 (P1) and point 21 (P2) so that a pressure drop (P1-P2) is maintained across the system. Coupling compounds such as activated monomers are supplied from reservoirs 31, 32, and 33. Additional reagents are supplied from reservoirs 15, 17, and 19. Of course, the monomer and coupling reagent reservoirs shown in Fig. 10 are representative of a potentially much larger series of reservoirs. The reagents and coupling compounds are combined at nodes 27, 28, and 29 before being directed to channel block 139. Mixing of the appropriate reagents and coupling compounds is controlled by valves at the nodes which are in turn controlled by electronic control 23. Waste fluids that have been directed across the substrate are removed through line 35.

The system displayed in Fig. 10 allows control of all channels in parallel by regulating only a few variables. For example, a constant pressure gradient is maintained across all channels simultaneously by fixing P1 and P2. Thus, the flow rate in each channel is dependent upon the cross-sectional area of the flow channel and the rheological properties of the fluids. Because the channels have a uniform cross-section and because the coupling compounds are typically provided as dilute solutions of a single solvent, a uniform flow rate is created across all channels. With this system the coupling time in all channels can be varied simultaneously by simply adjusting the pressure gradient across the system. The valves of the system are preferably controlled by a single electronic output from control 23.

The fanned channel array design shown in Fig. 7 provides for two separate channel blocks to be used in successive process



steps during a chemical synthesis. One block forms a horizontal array on the solid substrate, while the other block forms a vertical array. To create a matrix of intersecting rows and columns of chemical compounds, the solid substrate is transferred from one block to the other during successive process steps. While many experiments require only a single transfer from one block to the other during a series of process steps, the fanned channel array transfer block 75 illustrated in Figs. 11a and 11b provides one device for maintaining accurate registration of the solid substrate 71 relative to the channel blocks 79 during repeated transfers. In some embodiments, a single channel block can be used for horizontal and vertical arrays by simply rotating it by 90 degrees as necessary.

The transfer block is positioned with respect to the channel block so that the dimensional characteristics of the solid substrate are not used in the alignment. The transfer block 75 is aligned to the channel block by kinematic mount 81 while vacuum is switched from vacuum line 83 on the channel block to vacuum line 77 on the transfer block (during normal operation, a vacuum holds the substrate against the channel block). The substrate and transfer block are then moved and repositioned relative to the second channel block. Vacuum is then switched to the second channel block, retaining the substrate in proper alignment. This way, accurate registration can be assured between process steps regardless of variation in the dimensions of individual substrates. The transfer block system also maintains alignment of the matrix area during transfers to and from the flow cell during experiments utilizing both mechanical and light-directed process steps.

In some embodiments the channel block need not be utilized. Instead, in some embodiments, small "strips" of reagent are applied to the substrate by, for example, striping the substrate or channels therein with a pipettor. Such embodiments bear some resemblance to the spotting embodiments of this invention. According to other embodiments the channels will be formed by depositing a photoresist such as those used extensively in the semiconductor industry. Such materials include polymethyl methacrylate (PMMA) and its derivatives, and electron beam resists such as poly(olefin sulfones) and the like (more fully described in Ghandi, "VLSI Fabrication Principles," Wiley (1983) Chapter 10, incorporated herein by reference in its entirety for all purposes). According to these embodiments, a resist is deposited, selectively exposed, and etched, leaving a portion of the substrate exposed for coupling. These steps of depositing resist, selectively removing resist and monomer coupling are repeated to form polymers of desired sequence at desired locations.

In some embodiments, a resist can be used to activate certain regions of the substrate. Certain resist materials such as acid-generating polymers, for example, will release protons upon irradiation. According to these embodiments, a substrate covered  
5 with such material is irradiated through a mask or otherwise selectively irradiated so that the irradiated regions of the substrate are exposed to acidic conditions. Acid-labile protecting group on the substrate or oligomers on the substrate are removed, leaving an activated region. At this point, all or part of the  
10 resist may be removed. In preferred embodiments, the resist will be removed only in the activated regions, so that the channels are formed at the activated regions. Alternatively, the resist can be removed from the entire substrate. In this case, a separate channel block can then be contacted with the substrate to define flow  
15 channels, or a conventional VLSIPS™ procedure can be employed.

In preferred embodiments, the substrate is conventional glass, pyrex, quartz, any one of a variety of polymeric materials, or the like. Of course, the substrate may be made from any one of a variety of materials such as silicon, polystyrene, polycarbonate, or  
20 the like. In preferred embodiments the channel block is made of silicon or polychlorotrifluoroethylene, such as material known under the trade name Kelf™ 80 made by 3M, although a wide variety of materials such as polystyrene, polycarbonate, glass, elastomers such as Kalrez made by DuPont, various ceramics, stainless steel, or the  
25 like may be utilized.

The channels in the channel block are preferably made by machining, compression molding, injection molding, lithography, laser cutting, or the like depending upon the material of interest. In some embodiments employing larger channel blocks, the raised portions  
30 of the channels in the channel block are treated by lapping with lapping film (0.3  $\mu\text{m}$  grit). Such smooth surfaces provide good seals to the substrate without the use of a sealant and, therefore, without the possibility of leaving sealant material on the substrate when rotating the channel block. Preferably, all operations are conducted  
35 at substantially ambient temperatures and pressures.

A particularly preferred channel block is prepared by chemical etching of polished silicon wafers. Chemical etching is a widely used technique in integrated circuit fabrications. It can easily provide 60 or more 100 micron channels on a 12.8 mm region of  
40 a polished silicon wafer. Even after etching, the top (unetched) surface regions of the wafer retains the very flat profile of the unetched wafer. Thus, close contact with the substrate is ensured during flow cell operation.

In operation, the surface of the substrate is  
45 appropriately treated by cleaning with, for example, organic

solvents, methylene chloride, DMF, ethyl alcohol, or the like. Optionally, the substrate may be provided with appropriate linker molecules on the surface thereof. The linker molecules may be, for example, aryl acetylene, ethylene glycol oligomers containing from 2-10 monomers or more, diamines, diacids, amino acids, or combinations thereof. Thereafter, the surface is provided with protected surface active groups such as TBOC or FMOC protected amino acids. Such techniques are well known to those of skill in the art.

Thereafter, the channel block and the substrate are brought into contact forming fluid-tight channels bounded by the grooves in the channel block and the substrate. When the channel block and the substrate are in contact, a protecting group removal agent is, thereafter, directed through a first selected channel or group of channels by placing the pipettor on the flow inlet of the selected channel and, optionally, the vacuum source on the outlet of the channel. In the case of, for example, TBOC protected amino acids, this protecting group removal agent may be, for example, trifluoroacetic acid (TFA). This step is optionally followed by steps of washing to remove excess TFA with, for example, dichloromethane (DCM).

Thereafter, a first amino acid or other monomer A is directed through the first selected flow channel. Preferably this first amino acid is also provided with an appropriate protecting group such as TBOC, FMOC, NVOC, or the like. This step is also followed by appropriate washing steps. The of deprotection/coupling steps employed in the first group of channels are concurrently with or thereafter repeated in additional groups of channels. In preferred embodiments, monomer A will be directed through the first group of channels, monomer B will be directed through a second group of flow channels, etc., so that a variety of different monomers are coupled on parallel channels of the substrate.

Thereafter, the substrate and the channel block are separated and, optionally, the entire substrate is washed with an appropriate material to remove any unwanted materials from the points where the channels contact the substrate.

The substrate and/or block is then, optionally, washed and translated and/or rotated with the stage. In preferred embodiments, the substrate is rotated 90 degrees from its original position, although some embodiments may provide for greater or less rotation, such as from 0 to 180 degrees. In other embodiments, such as those discussed in connection with the device shown in Fig. 7, two or more different channel blocks are employed to produce different flow patterns across the substrate. When the channel block is rotated, it may simultaneously be translated with respect to the substrate. "Translated" means any relative motion of the substrate

and/or channel block, while "rotation" is intended to refer to rotation of the substrate and/or channel block about an axis perpendicular to the substrate and/or channel block. According to some embodiments the relative rotation is at different angles for different stages of the synthesis.

The steps of deprotection, and coupling of amino acids or other monomers is then repeated, resulting in the formation of an array of polymers on the surface of the substrate. For example, a monomer B may be directed through selected flow channels, providing the polymer AB at intersections of the channels formed by the channel block in the first position with the channels formed by the channel block after 90-degree rotation.

While rotation of the channel block is provided according to preferred embodiments of the invention, such rotation is not required. For example, by simply flowing different reagents through the channels, polymers having different monomer sequences may be formed. Merely by way of a specific example, a portion of the channels may be filled with monomer "A," and a portion filled with monomer "B" in a first coupling step. All or a portion of the first channels are then filled with a monomer "C," and all or a portion of the second channels are filled with a monomer "D," forming the sequences AB and CD. Such steps could be used to form 100 sequences using a basis set of 10 monomers with a 100-groove channel block.

In another embodiment, the invention provides a multichannel solid-phase synthesizer as shown in Fig. 12. In this embodiment, a collection of delivery lines such as a manifold or collection of tubes 1000 delivers activated reagents to a synthesis support matrix 1002. The collection of tubes 1000 may take the form of a rigid synthesis block manifold which can be precisely aligned with the synthesis support matrix 1002. The support matrix contains a plurality of reaction regions 1004 in which compounds may be immobilized or synthesized. In preferred embodiments, the reaction regions include synthesis frits, pads, resins, or the like.

The solutions delivered to the individual reactant regions of the support matrix flow through the reaction regions to waste disposal regions, recycling tank(s), separators, etc. In some embodiments, the reaction solutions simply pass through the reaction regions under the influence of gravity, while in other embodiments, the solutions are pulled or pushed through the reaction regions by vacuum or pressure.

The individual reaction regions 1004 of the support matrix are separated from one another by walls or gaskets 1006. These prevent the reactant solution in one reaction region from moving to and contaminating adjacent reaction regions. In one embodiment, the reaction regions are defined by tubes which may be

filled with resin or reaction mixture. The gasketing allows close contact between the support matrix 1002 and a "mask" (not shown). The mask serves to control delivery of a first group reactant solutions through predetermined lines (tubes) to a first set of reaction regions. By ensuring close contact between the delivery tubes 1000, the mask, and the support matrix 1002, the probability that reaction solutions will be accidentally added to the wrong reaction site is reduced.

After each process step, the mask can be changed so that a new group reactants is delivered to a new set of reaction regions. In this manner, a combinatorial strategy can be employed to prepare a large array of polymers or other compounds. In other embodiments, mechanisms other than masks can be employed to block the individual delivery tubes. For example, an array of control valves within the tubes may be suitable for some embodiments.

By adjusting the thickness of the synthesis support matrix, the quantity of immobilized material in the reaction regions can be controlled. For example, relatively thin support synthesis matrices can be used to produce small amounts of surface bound oligomers for analysis, while thicker support matrices can be used to synthesize relatively large quantities of oligomers which can be cleaved from the support for further use. In the latter embodiment, a collector having dimensions matching the individual synthesis supports can be employed to collect oligomers that are ultimately freed from the reaction matrix.

To illustrate the ability of this system to synthesize numerous polymers, a square synthesis matrix measuring 10 cm along each side and having 5 mm reaction regions separated by 5 mm wide gaskets provides 100 individual syntheses sites (reaction regions). By reducing the size of the reaction regions to 2.5 mm on each side, 400 reactions regions become available.

While linear grooves are shown herein in the preferred aspects of the invention, other embodiments of the invention will provide for circular rings or other shapes such as circular rings with radial grooves running between selected rings. According to some embodiments, channel blocks with different geometric configurations will be used from one step to the next, such as circular rings in one step and linear stripes in the next. Fig. 13a illustrates one of the possible arrangements in which the channels 409 are arranged in a serpentine arrangement in the channel block 407. Through appropriate translation and/or rotation of the channel block, polymers of desired monomer sequence are formed at the intersection of the channels during successive polymer additions, such as at location 501, where the intersection of a previous or subsequent set of channels is shown in dashed lines. Fig. 13b

illustrates another arrangement in which channels (in this case without flow paths 413) are provided in a linear arrangement, with groups 503 and 505 located in adjacent regions of the substrate and extending only a portion of the substrate length.

5 In some embodiments of the invention, the various reagents, such as those containing the various monomers, are not pumped through the apertures 413. Instead, the reagent is placed in one of the grooves, such as the grooves 409 shown in Fig. 13b, filling the groove. The substrate is then placed on top of the  
10 channel block, and the exposed portions of the substrate are permitted to react with the materials in the grooves. In preferred embodiments, the channels are of the same width as the raised regions between the channels. According to these embodiments, the substrate may then be moved laterally by one channel width or an integer  
15 multiple of a channel width, permitting reaction with and placement of monomers on the regions between the channels in a previous coupling step. Thereafter, the substrate or channel block will be rotated for the next series of coupling steps.

In preferred embodiments, the process is repeated to  
20 provide more than 10 different polymer sequences on the surface of the substrate. In more preferred embodiments, the process is repeated to provide more than  $10^2$ ,  $10^3$ ,  $10^4$ ,  $10^5$ ,  $10^6$ , or more polymer sequences on a single substrate. In some embodiments the process is repeated to provide polymers with as few as two monomers, although  
25 the process may be readily adapted to form polymers having 3, 4, 5, 6, 10, 15, 20, 30, 40, 50, 75, 100 or more monomers therein.

According to preferred embodiments, the array of polymer sequences is utilized in one or more of a variety of screening processes, one of which is described in copending application U.S.  
30 Serial No. 796,947, filed on November 22, 1991 and incorporated herein by reference for all purposes. For example, according to one embodiment, the substrate is then exposed to a receptor of interest such as an enzyme or antibody. According to preferred embodiments, the receptor is labelled with fluorescein, or otherwise labelled, so  
35 as to provide for easy detection of the location at which the receptor binds. According to some embodiments, the channel block is used to direct solutions containing a receptor over a synthesized array of polymers. For example, according to some embodiments the channel block is used to direct receptor solutions having different  
40 receptor concentrations over regions of the substrate.

According to most preferred embodiments, amplification of the signal provided by way of fluorescein labelling is provided by exposing the substrate to the antibody of interest, and then exposing the substrate to a labelled material which is complementary  
45 to the antibody of interest and which preferably binds at multiple

locations of the antibody of interest. For example, in one specific embodiment, if a mouse antibody is to be studied, a labelled second antibody may be exposed to the substrate which is, for example, goat antimouse. Such techniques are described in PCT Publication No.

5 WO92/10092, previously incorporated herein by reference.

#### V. Spotting Embodiments

According to some embodiments, monomers (or other reactants) are deposited from a dispenser in droplets that fill  
10 predefined regions. For example, in a single coupling step, the dispenser deposits a first monomer in a series of predefined regions by moving over a first region, dispensing a droplet, moving to a second region, dispensing a droplet, and so on until the each of the selected regions has received the monomer. Next the dispenser  
15 deposits a second monomer in a second series of predefined regions in much the same manner. In some embodiments, more than one dispenser may be used so that more than one monomer are simultaneously deposited. The monomers may react immediately on contact with the reaction regions or may require a further activation step, such as  
20 the addition of catalyst. After some number of monomers have been deposited and reacted in predefined regions throughout the substrate, the unreacted monomer solution is removed from the substrate. This completes a first process step.

For purposes of this embodiment, the spacing between the  
25 individual reaction regions of the substrate preferably will be less than about 3 mm, and more preferably between about 5 and 100  $\mu\text{m}$ . Further, the angular relation between the regions is preferably consistent to within 1 degree and more preferably to within 0.1 degree. Preferably, the substrate will include at least about 100  
30 reaction regions, more preferably at least about 1000 reaction regions, and most preferably at least about 10,000 reaction regions. Of course, the density of reaction regions on the substrate will vary. In preferred embodiments, there are at least about 1000 reaction regions per  $\text{cm}^2$  of substrate, and more preferably at least  
35 about 10,000 regions per  $\text{cm}^2$ .

To deposit reactant droplets consistently at precisely specified regions, a frame of reference common to the delivery instrument and the substrate is required. In other words, the reference coordinates of the instrument must be accurately mapped  
40 onto the reference coordinates of the substrate. Ideally, only two reference points on the substrate are necessary to map the array of polymer regions completely. The dispenser instrument locates these reference points and then adjusts its internal reference coordinates to provide the necessary mapping. After this, the dispenser can move  
45 a particular distance in a particular direction and be positioned

directly over a known region. Of course, the dispenser instrument must provide precisely repeatable movements. Further, the individual regions of the array must not move with respect to the reference marks on the substrate after the reference marks have been formed.

5 Unfortunately, pressing or other mechanical operations commonly encountered during fabrication and use of a substrate can warp the substrate such that the correspondence between the reference marks and the reaction regions is altered.

Thus, in preferred embodiments, a substrate containing  
10 both "global" and "local" reference marks is employed. In preferred embodiments, two global reference marks are conveniently located on the substrate to define the initial frame of reference. When these points are located, the dispenser instrument has an approximate map of the substrate and the predefined regions therein. To assist in  
15 locating the exact position of the regions, the substrate is further subdivided into local frames of reference. Thus, in an initial, "course" adjustment, the dispenser is positioned within one of the local frames of reference. Once in the local region, the dispensing instrument looks for local reference marks to define further a local  
20 frame of reference. From these, the dispenser moves exactly to the reaction region where the monomer is deposited. In this manner, the effects of warpage or other deformation can be minimized. The number of local reference marks is determined by the amount of deformation expected in the substrate. If the substrate is sufficiently rigid so  
25 that little or no deformation will occur, very few local reference marks are required. If substantial deformation is expected, however, more local reference marks are required.

In order to locate the appropriate reference point initially and align the dispenser with respect to it, a vision or  
30 blind system may be employed. In a vision system, a camera is rigidly mounted to the dispenser nozzle. When the camera locates the reference point(s), the dispenser is known to be a fixed distance and direction away from the point, and a frame of reference is established. Blind systems of the present invention locate the  
35 reference point(s) by capacitive, resistive, or optical techniques, for example. In one example of an optical technique, a laser beam is transmitted through or reflected from the substrate. When the beam encounters a reference mark, a change in light intensity is detected by a sensor. Capacitive and resistive techniques are similarly  
40 applied. A sensor registers a change in capacitance or resistivity when a reference point is encountered.

Starting at a single reference point, the dispenser is translated from one reaction region to other regions of the substrate by a correct distance in the correct direction (this is the "dead  
45 reckoning" navigational technique). At each stop, the dispenser



deposits correctly metered amounts of monomer. Analogous systems widely used in the microelectronic device fabrication and testing arts can move at rates of up to 3-10 stops per second. The translational (X-Y) accuracy of such systems is well within 1  $\mu\text{m}$ .

- 5 Translational mechanisms for moving the dispenser are preferably equipped with closed loop position feedback mechanisms (encoders) and have insignificant backlash and hysteresis. In preferred embodiments, the translation mechanism has a high resolution, i.e. better than one motor tick per encoder count.
- 10 Further, the electro-mechanical mechanism preferably has a high repeatability relative to the reaction region diameter travel distance (typically  $\pm 1\mu\text{m}$  or better).

- To deposit a drop of monomer solution on the substrate accurately, the dispenser nozzle must be placed a correct distance above the surface. In one embodiment, the dispenser tip preferably will be located about 5-50  $\mu\text{m}$  above the substrate surface when a five nanoliter drop is released. More preferably, the drop will be about 10  $\mu\text{m}$  above the substrate surface when the drop is released. The degree of control necessary to achieve such accuracy is attained with
- 15 a repeatable high-resolution translation mechanism of the type described above. In one embodiment, the height above the substrate is determined by moving the dispenser toward the substrate in small increments, until the dispenser tip touches the substrate. At this point, the dispenser is moved away from the surface a fixed number of
- 20 increments which corresponds to a specific distance. From there the drop is released to the cell below. Preferably, the increments in which the dispenser moves less than about 5  $\mu\text{m}$  and more preferably less than about 2  $\mu\text{m}$ .

- In an alternative embodiment, the dispenser nozzle is encircled by a sheath that rigidly extends a fixed distance beyond the dispenser tip. Preferably, this distance corresponds to the distance the solution drop will fall when delivered to the selected reaction region. Thus, when the sheath contacts the substrate surface, the movement of the dispenser is halted and the drop is
- 25 released. It is not necessary in this embodiment to move the dispenser back, away from the substrate, after contact is made. The point of contact with the surface can be determined by a variety of techniques such as by monitoring the capacitance or resistance between the tip of the dispenser (or sheath) and the substrate below.
- 30 A rapid change in either of these properties is observed upon contact with the surface.

To this point, the spotting system has been described

only in terms of translational movements. However, other systems may also be employed. In one embodiment, the dispenser is aligned with respect to the region of interest by a system analogous to that employed in magnetic and optical storage media fields. For example, the region in which monomer is to be deposited is identified by a track and sector location on the disk. The dispenser is then moved to the appropriate track while the disk substrate rotates. When the appropriate cell is positioned below the dispenser (as referenced by the appropriate sector on the track), a droplet of monomer solution is released.

Control of the droplet size may be accomplished by various techniques. For example, in one embodiment, a conventional micropipetting instrument is adapted to dispense droplets of five nanoliters or smaller from a capillary. Such droplets fit within regions having diameters of 300  $\mu\text{m}$  or less when a non-wetting mask of the invention is employed.

In another embodiment, the dispenser is a piezoelectric pump that generates charged droplets and guides them to the reaction region by an electric field in a manner analogous to conventional ink-jet printers. In fact, some ink-jet printers can be used with minor modification by simply substituting a monomer containing solution for ink. For example, Wong *et al.*, European Patent Application 260 965, incorporated herein by reference for all purposes, describes the use of a commercial printer to apply an antibody to a solid matrix. In the process, a solution containing the antibody is forced through a small bore nozzle that is vibrating in a manner that fragments the solution into discrete droplets. The droplets are subsequently charged by passing through an electric field and then deflected onto the matrix material.

A conventional ink drop printer includes a reservoir in which ink is held under pressure. The ink reservoir feeds a pipe which is connected to a nozzle. An electromechanical transducer is employed to vibrate the nozzle at some suitable high frequency. The actual structure of the nozzle may have a number of different constructions, including a drawn glass tube which is vibrated by an external transducer, or a metal tube vibrated by an external transducer (e.g. a piezoelectric crystal) or a magnetostrictive metal tube which is magnetostrictively vibrated. The ink accordingly is ejected from the nozzle in a stream which shortly thereafter breaks into individual drops. An electrode may be present near the nozzle to impart a charge to the droplets. Conventional ink drop dispensers are described in U.S. Patent Nos. 3,281,860 and 4,121,222, which are incorporated by reference herein for all purposes.

In a different preferred embodiment, the reactant solutions are delivered from a reservoir to the substrate by an

electrophoretic pump. In this device, a thin capillary connects a reservoir of the reactant with the nozzle of the dispenser. At both ends of the capillary, electrodes are present to provide a potential difference. As is known in the art, the speed at which a chemical species travels in a potential gradient of an electrophoretic medium is governed by a variety of physical properties, including the charge density, size, and shape of the species being transported, as well as the physical and chemical properties of the transport medium itself. Under the proper conditions of potential gradient, capillary dimensions, and transport medium rheology, a hydrodynamic flow will be set up within the capillary. Thus, in an electrophoretic pump of the present invention, bulk fluid containing the reactant of interest is pumped from a reservoir to the substrate. By adjusting the appropriate position of the substrate with respect to the electrophoretic pump nozzle, the reactant solution is precisely delivered to predefined reaction regions.

In one particularly useful application, the electrophoretic pump is used to produce an array containing various fractions of an unknown reactant solution. For example, an extract from a biological material such as leaf or a cell culture might contain various unknown materials, including receptors, ligands, alkaloids, nucleic acids, and even biological cells, some of which may have a desired activity. If a reservoir of such extract is electrophoretically pumped, the various species contained therein will move through the capillary at different rates. Of course, the various components being pumped should have some charge so that they can be separated. If the substrate is moved with respect to the dispenser while the extract components are being separated electrophoretically, an array containing various independent species is produced. This array is then tested for activity in a binding assay or other appropriate test. Those elements of the array that show promising activity are correlated with a fraction of the extract which is subsequently isolated from another source for further study. In some embodiments, the components in the extract solution are tagged with, for example, a fluorescent label. Then, during the process of delivering the solution with the electrophoretic pump, a fluorescence detector determines when labeled species are being deposited on the substrate. In some embodiments, the tag selectively binds to certain types of compounds within the extract, and imparts a charge to those compounds.

Other suitable delivery means include osmotic pumps and cell (biological) sorters. An osmotic pump delivers a steady flow of solution for a relatively long period. The construction of such pumps is well-known in the art, generally incorporating a solution of the extract of interest within a solvent permeable bag. Osmotic

pressure is applied to the extract solution by solvent molecules diffusing across the bag to equalize a concentration difference. The extract is thus forced out of a nozzle in the bag at a constant rate. Cell sorters are also well-known in the art, and can be used in applications where it is desirable to apply single biological cells to distinct locations on the substrate.

Although the above embodiments have been directed to systems employing liquid droplets, minuscule aliquots of each test substance can also be delivered to the cell as miniature pellets. Such pellets can be formed from the compound of interest (e.g. ligands for use in an affinity assay) and one or more kinds of inert binding material. The composition of such binders and methods for the preparation of the pellets will be apparent to those of skill in the art. Such "mini-pellets" will be compatible with a wide variety of test substances, stable for long periods of time, suitable for easy withdrawal from the storage vessel and dispensing (i.e., non-tacky, preferably suspendable in a liquid such as physiological buffer), and inert with respect to the binding activity of receptors.

In preferred embodiments, the reactant solutions in each predefined region are prevented from moving to adjacent regions by appropriate barriers or constraining regions. For example to confine aqueous monomer solutions, a hydrophilic material is used to coat the reaction regions, while a hydrophobic material is used in preferred embodiments to coat the region surrounding the individual reaction regions. Of course, when non-aqueous or nonpolar solvents are employed, different surface coatings are generally preferred. By choosing appropriate materials (substrates, hydrophobic coatings, and reactant solvents), the contact angle between the droplet and the substrate is advantageously controlled. Large contact angles between the reactant droplets and the substrate are desired because the solution then wets a relatively small reaction region with shallow contact angles, on the other hand, the droplet wets a larger area. In extreme cases, the droplet will spread to cover the entire surface.

The contact angle is determined by the following expression, known as Young's equation:

$$\cos \theta = (\sigma_{sa} - \sigma_{sl}) / \sigma_{la}$$

where  $\theta$  is the wetting angle,  $\sigma_{sa}$  is the solid-air tension,  $\sigma_{sl}$  is the solid-liquid tension, and  $\sigma_{la}$  is the liquid-air surface tension. The values of these surface tensions are governed by thermodynamic considerations including the chemical constituents of the liquid and the solid substrate. The liquid-air surface tension for various


chemicals is easily measured by a variety of techniques such as those described in Adamson, Physical Chemistry of Surfaces, John Wiley and Sons, 5th Ed. (1990) which is incorporated herein by reference for all purposes. The difference of the solid-liquid and solid-air tensions can, for a given system, be determined empirically from a Zisman plot. In this approach, the contact angles are measured for a homologous series of liquids on a given solid surface. For some liquid in the series, a "critical contact angle" is observed, beyond which lower surface tension liquids wet the surface. The liquid-air surface tension of the liquid at this critical contact angle is assumed to be the surface tension of the solid. This approach has been found to provide quite reasonable results for low energy solids such as Teflon, polyethylene, hydrocarbons, etc. The information gained from such studies is used to optimize substrate compositions to increase wetting angles for given reactant solutions in the array.

Methods for controlling chemical composition and therefore the local surface free energy of a substrate surface include a variety of techniques apparent to those skilled in the art. Chemical vapor deposition and other techniques applied in the fabrication of integrated circuits can be applied to deposit highly uniform layers on selected regions of a surface. As a specific example, the wettability of a silicon wafer surface has been manipulated on the micrometer scale through a combination of self-assembled monolayer depositions and micromachining. See Abbott et al., "Manipulation of the Wettability of Surfaces on the .1 to 1 Micrometer Scale Through Micromachining and Molecular Self-Assembly" *Science*, 257 (Sept. 4, 1992) which is incorporated herein by reference for all purposes.

In a preferred embodiment, the perimeters of the individual regions are formed on a hydrophilic substrate defined by selectively removing hydrophobic protecting groups from the substrate surface. For example, a mono-layer of hydrophobic photoprotecting groups can be coupled to, for example, linker molecules attached to the substrate surface. The surface then is selectively irradiated (or otherwise activated by, for example, acid) through a mask to expose those areas where the reaction regions are to be located. This cleaves the protecting groups from the substrate surface, causing the reaction regions to be less hydrophobic than the surrounding area. This process produces a high density of reaction regions on the substrate surface. Because hydrophobic materials have lower surface free energies (surface tensions) than water, the solution droplet in the cell beads rather than spreads.


In some preferred embodiments, the substrate is prepared by first covalently attaching a monolayer of the desired reactive functional group (e.g. amine, hydroxyl, carboxyl, thio, etc.), which

is protected by a hydrophobic photolabile protecting moiety. If the substrate provides a glass surface, the monolayer may be deposited by a silanation reaction as shown below



15 In the above structures, Y is a spacer group such as a polymethylene chain, X is a reactive protected group such as NH, C(O)O, O, S, etc., and Pr is a hydrophobic photolabile protecting group.

20 In an alternative preferred embodiment shown below, the substrate surface is first derivatized by, for example, a silanation reaction with appropriates to provide an amine layer. A molecule including a spacer, a reactive group, and a photolabile group is then coupled to the surface.




35

The photolabile protecting group should be sufficiently hydrophobic as to render the substrate surface substantially non-wettable. Removal of the protecting group in specific areas by exposure to light through a suitable mask, liberates the reactive functional groups. Because these groups are hydrophilic in character, they will render the substrate wettable in the exposed regions.

45 The class of nitrobenzyl protecting groups, which is exemplified by the nitroveratryl group, imparts significant

hydrophobicity to glass surfaces to which a member of the class is attached. The hydrophobicity of the basic nitrobenzyl protecting group is enhanced by appending group chain hydrocarbon substituent. Exemplary hydrophobic chains include  $C_{12}H_{25}$  (lauryl) or  $C_{18}H_{37}$  (stearyl) substituents. The syntheses of suitably activated forms (bromide, chloromethyl ether, and oxycarbonyl chloride) of a typical protecting group is schematically outlined in Fig. 14.

The spacer group ("Y") contributes to the net hydrophobic or hydrophilic nature of the surface. For example, those spacers consisting primarily of hydrocarbon chains, such as  $-(CH_2)_n-$ , tend to decrease wettability. Spacers including polyoxyethylene  $-(CH_2CH_2O)_n$ , or polyamide  $-(CH_2CONH)_n$  chains tend to make the surface more hydrophilic. An even greater effect is achieved by using spacer groups which possess, in addition to the protected functional group, several "masked" hydrophilic moieties. This is illustrated below.



In preferred embodiments, the hydrophilic reaction regions is a two-dimensional circle or other shape having an aspect ratio near one (i.e. the length is not substantially larger or smaller than the width). However, in other embodiments, the hydrophilic region may take the form of a long channel which is used to direct flowing reactants in the manner described above.

In still other embodiments, the reaction regions are three-dimensional areas defined by, for example, gaskets or dimples on the substrate surface. The dimples or gaskets may also act as identification marks directing the dispenser to the region of interest.

If the solvent (or other liquid used to deliver the reactant) has a sufficiently high vapor pressure, evaporation can cause the reactant concentration to increase. If left unchecked, this process ultimately causes the solute to precipitate from solution. The effects of evaporation can be minimized by sealing selected regions of the substrate when they need not be accessible. Alternatively, the partial pressure of volatile reagents can be adjusted so that the liquid and vapor phase fugacities are equalized and the thermodynamic force driving evaporation is reduced. The partial pressure of the reagents may be increased by providing a relatively large reservoir of volatile reagents in a sealed chamber. For example, solvents having a low vapor pressure under the conditions of interest can be used. In some cases, evaporation can be further controlled by application of a film or coverplate having a reverse array pattern. Other methods of preventing evaporation are well-known in the physical chemical arts and may be used in the present invention.

In some preferred embodiments, evaporation is advantageously employed to accelerate hybridization of target oligonucleotides with immobilized oligonucleotides in the reaction regions. In one specific embodiment, fluorescently tagged or otherwise labelled target oligonucleotides in solution (e.g., a solution containing a salt such as ammonium acetate or magnesium chloride) are delivered to reaction regions containing immobilized probe oligonucleotides. As the volatile salt solution evaporates from the reactant droplet (in the same manner as solvent evaporates from an ink droplet deposited by an ink jet printer), a locally high concentration ratio of target to probe oligonucleotide results, accelerating hybridization. If hybridization is carried out at room temperature, ten minutes to a few hours are typically required to complete the reaction. After sufficient time, the unhybridized DNA is washed or otherwise removed from the substrate. Finally, the substrate is imaged to detect regions in which the probe and target DNA have hybridized. Of course, evaporation can be advantageously employed to increase the local concentration of non-DNA solutes in a variety of reactions besides hybridization. For example in some embodiments, receptor solutions are sufficiently volatile that the local receptor concentration increases in the reaction regions containing peptides, for example, to be screened.



The arrays produced according to the above spotting  
embodiments are generally used in much the same manner as the arrays  
produced by the flow channel embodiments described above. For  
example, the arrays can be used in screening with fluorescein  
5 labelled receptors as described in PCT Publication No. WO92/10092,  
previously incorporated by reference.

#### VI. Alternative Embodiments

According to some embodiments of the invention,  
10 microvalve structures are used to form channels along selected flow  
paths on the substrate. According to these embodiments, an array of  
microvalves is formed and operated by an overlying or underlying  
array of electrodes that is used to energize selected valves to open  
and close such valves.

15 Fig. 15 illustrates such a structure, Fig. 15a  
illustrating the system in end view cross-section and Fig. 15b  
illustrating the system in top view. The structure shown therein  
provides for only two synthesis chambers for the purpose of clarity,  
but in most embodiments a far greater number of chambers will be  
20 provided. Microvalves are discussed in detail in, for example,  
Zdeblick, U.S. Patent No. 4,966,646, and Knutti, "Advanced Silicon  
Microstructures," ASICT Conference (1989), both incorporated herein  
by reference for all purposes.

As shown therein, a substrate 602 is provided with a  
25 plurality of channels 604 formed using photolithographic, or other  
related techniques. The channels lead up to a synthesis chamber 606.  
At the end of each channel is valve structure 608. As shown in  
Fig. 15, the channels lead up to the chambers, but may be isolated  
from the chambers by the valves. Multiple valves may be provided for  
30 each chamber. In the particular structure shown in Fig. 15, the  
right valve on the left chamber and the left valve on the right  
chamber are open while the remaining valves are closed. Accordingly,  
if reagent is delivered to the top of the substrate, it will flow  
through the open channel to and through the chamber on the left, but  
35 not the one on the right. Accordingly, coupling steps may be  
conducted on the chamber with selected reagents directed to selected  
chambers, using the techniques discussed above.

According to some embodiments, a valve is supplied on one  
side of the chamber 606, but the valve on the opposite side is  
40 replaced by a semi-permeable membrane. According to these  
embodiments, it becomes possible to flow a selected reagent into the  
chamber 606 and, thereafter, flow another selected reagent through  
the flow channel adjacent the semi-permeable membrane. The semi-  
permeable membrane will permit a portion of the material on one side

or the other to pass through the membrane. Such embodiments will be useful in, for example, cell studies.

Screening will be performed by, for example, separating or cutting two halves of the device, enabling screening by, for example, contacting with a fluorescein labelled antibody, or the like followed by photodetection.

Figs. 16a and 16b illustrate another alternative embodiment of the invention which combines the mechanical polymer synthesis techniques disclosed herein with light-directed synthesis techniques. According to these embodiments, a substrate 401 is irradiated in selected regions, shown as the stripes in Fig. 16a. The surface of the substrate is provided with photoremovable groups in accordance with PCT Publication No. WO92/10092 (previously incorporated by reference) on, for example, amine groups in the specific case of peptide synthesis. During this step regions 701, 702, and 703 of the substrate, among others, are deprotected, leaving remaining regions of the substrate protected by photoremovable groups such as nitroveratryl oxycarbonyl ("NVOC"). According to a specific embodiment of the invention the widths of the irradiated regions equal the widths of the protected regions of the substrate.

Thereafter, as shown in Fig. 16b the substrate is contacted with a channel block 407. In the particular embodiment shown in Fig. 16b, the channels 704, 705, and 707 are aligned with the regions 701, 702, and 703, respectively, on the substrate 401. As will be apparent, specific embodiments of the invention provide for irradiated regions and channels in the form of stripes, which are aligned during this step. Other embodiments, however, will provide for other shapes of irradiated regions and channels, and other relative orientations of the irradiated regions and channels. The channel block and substrate will be aligned with, for example, an alignment mark placed on both the substrate and the channel block. The substrate may be placed on the channel block with, for example, a vacuum tip.

Thereafter, a selected reagent is flowed through or placed in the channels in the channel block for coupling to the regions which have previously been exposed to light. As with the flow channel embodiments described above, the substrate may be placed in contact with a prefilled channel block in some embodiments to avoid compression of the channel block to the substrate and dead spots during pumping. According to preferred aspects of the invention, a different reagent flows through each of the channels 701, 702, and 703 such as, for example, a reagent containing monomers A, B, and C. The process may then, optionally, involve a second coupling step in which the substrate is translated by, e.g., one

channel width, to provide coupling of a monomer in the regions between the original channels.

Thereafter, the process of directed irradiation by light, followed by coupling with the channel block is repeated at the previously unexposed regions. The process is then preferably repeated again, with the stripes of the mask and the channel block rotated at, for example, 90 degrees. The coupling steps will provide for the formation of polymers having diverse monomer sequences at selected regions of the substrate through appropriate translation of the mask and substrate, and through appropriate mask selection. Through a combination of the light-directed techniques and the mechanical flow channel techniques disclosed herein, greater efficiency in forming diverse sequences is achieved, because multiple monomers are coupled in a single irradiation/coupling step.

In light-directed methods, the light shown through the mask is diffracted to varying degrees around the edges of the dark regions of the mask. Thus, some undesired removal of photosensitive protecting groups at the edges of "dark" regions occurs. This effect is exacerbated by the repeated mask translations and subsequent exposures, ultimately leading to inhomogeneous synthesis sites at the edges of the predefined regions. The effect is, of course, dependent upon the thickness of the glass substrate and the angle at which the light is diffracted. If the mask is positioned on the "backside" of the substrate, a diffraction angle of  $2.5^\circ$  and a substrate thickness of 0.7 mm creates a  $60\text{ }\mu\text{m}$  strip of light (of variable intensity) flanking each edge. For a 0.1 mm thick substrate, the strip is approximately  $5\text{ }\mu\text{m}$  wide.

To reduce these "bleed-over" effects of diffraction, a pinhole mask may be employed to activate and/or define reaction regions of the substrate. Thus, for example, light shown through the pinhole mask is directed onto a substrate containing photoremovable hydrophobic groups. The groups in the illuminated regions are then removed to define hydrophilic reaction regions. In one specific embodiment, the pinhole mask contains a series of circular holes of defined diameter and separation, e.g.,  $20\text{ }\mu\text{m}$  diameter holes spaced  $50\text{ }\mu\text{m}$  apart. In some preferred embodiments, a stationary pinhole mask is sandwiched between the substrate and a translational mask of the type described in PCT Publication No. WO92/10092. In this manner selected regions of the substrate can be activated for polymer synthesis without bleed-over. The translational mask is used to illuminate selected holes of the stationary pinhole mask, and is aligned such that its edges dissect the distance separating the holes of the stationary mask thereby eliminating diffractive removal of photoprotecting groups at neighboring sites. Because there is negligible bleed-over incident light, inhomogeneous synthesis at

5 sites juxtaposed along the edge is eliminated. The resulting circular sites do, of course, contain variable sequence density due to diffraction at the edges of the pinhole mask, but the sequences at each predefined region are homogeneous. In addition, each synthesis region is surrounded by a "dark" region when the substrate is probed with a labeled target. Thus, no bleed-over fluorescence signal is introduced by binding at neighboring sites.

10 A pinhole mask containing 20  $\mu\text{m}$  circular holes separated by 50  $\mu\text{m}$  requires a total synthesis area for the complete set of octanucleotides of only 1.78  $\text{cm}^2$ . For a given pinhole mask, thinner substrates allow for smaller reaction sites separated by larger distances. However, the area from which reliable data can be obtained is also reduced when smaller sites are used. The density of reaction sites is ultimately determined by the diffraction angle and the distance between the pinhole mask and the reaction regions (typically the substrate thickness).

15 Although the discussion so far has focused upon circular pinholes, other shapes such as slots, squares, crescents, etc. may be employed as is appropriate for the selected delivery method. Thus, for some flow channel embodiments, linear or serpentine slots may be desired.

20 In alternative preferred embodiments, the pinhole mask takes the form of a layer coated on the substrate. This avoids the need for a separate stationary mask to generate the dot pattern. In addition, the surface layer provides well defined synthesis regions in which to deposit reactants according to the spotting embodiments described above. Further, the surface pinhole mask is conveniently embossed with local reference coordinates for use in navigational systems used to deliver monomer solutions to proper regions as described above. Preferred pinhole masks are made from opaque or reflective materials such as chrome.

## VI. Examples

### A. Leak Testing

35 An initial experiment was conducted using a flow channel device to ensure that solutions could be delivered to selected locations of a substrate and be prevented from contacting other areas. Additionally, the experiment was used to demonstrate that reagents could be delivered in a uniform manner.

40 Accordingly, a flat piece of conventional glass having dimensions of about 42 mm x 42 mm was derivatized with aminopropyltriethoxysilane. The entire slide was deprotected and washed using conventional techniques. A fluorescein marker of FITC was then injected into flow channels formed when a block of Kelf™ 81 with 10 channels of 1 mm depth and 1 mm width were brought into

45

contact with the substrate. The fluorescein marker was in a solution of DMF and flowed through the channels by injecting the material into the groove with a manual pipet.

Fluorescein dye was similarly injected into every other  
 5 channel in the block, the block was rotated, and the process was repeated. The expected resulting plot of fluorescent intensity versus location is schematically illustrated in Fig. 17. Dark regions are shown at the intersections of the vertical and horizontal stripes, while lighter grey at non-intersecting regions of the  
 10 stripes. The dark grey regions indicate expected regions of high dye concentration, while the light regions indicate regions of expected lower dye concentration.

Fig. 18 is a mapping of fluorescence intensity of a portion of an actual slide, with intensity data gathered according to  
 15 the methods of PCT Publication No. WO92/10092, previously incorporated by reference. The results agree closely with the expected results, exhibiting high fluorescence intensity at the intersection of the channels (about 50% higher than non-intersecting regions of the stripes), and lower fluorescence intensity at other  
 20 regions of the channels. Regions which were not exposed to fluorescence dye show little activity, indicating a good signal-to-noise ratio. Intersections have fluorescence intensity about 9x as high as background. Also, regions within the channels show low variation in fluorescence intensity, indicating that the regions are  
 25 being evenly treated within the channels.

#### B. Formation of YGGFL

The system was used to synthesize four distinct peptides: YGGFL (SEQ. ID NO:1), YpGFL (SEQ. ID NO:2), pGGFL (SEQ. ID NO:3), and  
 30 ppGFL (the abbreviations are included in Stryer, Biochemistry, Third Ed. (1988), previously incorporated herein by reference; lower case letters indicate D-optical isomers and upper case letters indicate L-optical isomers). An entire glass substrate was derivatized with TBOC-protected aminopropyltriethoxysilane, deprotected with TFA,  
 35 coated with FMOC-protected caproic acid (a linker), deprotected with piperidine, and coated with FMOC-protected Glycine-Phenylalanine-Leucine (GFL).

This FMOC-GFL-coated slide was sealed to the channel block, and all 10 grooves were deprotected with piperidine in DMF.  
 40 After washing the grooves, FMOC Glycine (G) was injected in the odd grooves, and FMOC d-Proline (p) was injected in the even grooves. After a two-hour coupling time, using standard coupling chemistry, all grooves were washed with DMF. The grooves were vacuum dried, the block removed and rotated 90 degrees. After resealing, all grooves  
 45 were deprotected with piperidine in DMF and washed. FMOC Tyrosine

(Y) was injected in the odd grooves, and FMOC p in the even grooves. After coupling the grooves were washed and vacuum dried. Accordingly, 25 regions of each of the compounds YGGFL, YpGFL, pGGFL, and ppGFL were synthesized on the substrate. The substrate was removed and stained with FITC-labelled antibodies (Herz antibody 3E7).

A section of the resulting slide illustrating fluorescence intensity is shown in Fig. 19. White squares are in locations of YGGFL. The darkest regions are pGGFL and ppGFL. The YGGFL sites were the most intense, followed by the YpGFL sites. The pGGFL and ppGFL intensities were near background levels, consistent with expected results with the Herz antibody.

Quantitative analysis of the results show overall intensity ratios for YGGFL:YpGFL:pGGFL:ppGFL as 1.7:1.5:1.1:1.0. However, since there is a large standard deviation on the YGGFL and YpGFL, comparing all the sites with each other may not accurately represent the actual contrasts. Comparing the intensities of sites within the same "stripe" gives larger contrasts, although they remain on the order of 2:1.

#### C. 100 Micron Channel Block

A grid pattern of fluorescein isothiocyanate coupled to a substrate was made by using a flow cell of this invention. A two by three inch NVOC-derivatized substrate was photolyzed through a mask to produce 400 micron activated bands on one axis. An etched silicon channel block having 64 parallel 100 micron channels separated by 100 micron walls was then clamped to the substrate on the other axis (i.e., perpendicular to the axis of 400 micron activated bands). The clamping assembly consisting of aluminum top and bottom clamp plates was used. Pressure was applied by tightening two bolts with a torque wrench to 400 psi. A 7 mM fluorescein isothiocyanate solution was flowed through the channels by pipetting directly to exposed channel ends.

An image of the substrate (Fig. 20) showed regions of high fluorescence indicating that the fluorescein had bound to the substrate. White squares indicating fluorescein binding were present as 400 micron horizontal stripes on the photolyzed regions within the 100 micron vertical flow paths. Contrast ratios of 8:1 were observed between the channels and the channel spacings. This demonstrates the nearly complete physical isolation of fluid passing through 100 micron channels under 400 psi of clamping pressure.

#### D. Channel Matrix Hybridization Assay

A center region of a two by three inch slide was derivatized with bis(2-Hydroxyethyl) aminopropyltriethoxy silane.

Six nucleosides were then coupled to the entire reaction region using a synthesis process consisting of deprotection, coupling, and oxidation steps for each monomer applied. These first six nucleosides were coupled in a reaction region defined by a 0.84 inch diameter circular well in an aluminum template clamped to the two by three inch slide.

The seventh and eighth monomers were applied to the substrate by flowing monomer solutions through 100 micron channels in an etched silicon channel block (employed in Example C above). The seventh base was coupled along the long axis (vertical) of the two-inch by three-inch slide, and the eighth base perpendicular to the seventh, along the short axis (horizontal) of the slide. This defined an active matrix region of 1.28 by 1.28 cm having a density of 2,500 reaction regions per square centimeter.

The channel block was centered over the reaction region and clamped to the substrate using a clamping assembly consisting of machined aluminum plates. This aligned the two inch by three inch substrate relative to the channel block in the desired orientation. Rotation of the top clamp plate and channel block relative to the bottom clamp plate and substrate between the seventh and eighth coupling steps provided for the matrix of intersecting rows and columns.

In the top clamp plate, fluid delivery wells were connected to laser-drilled holes which entered individual channels from the back surface of the channel block. These delivery wells were used to pipette coupling reagents into channels while the channel block was clamped to the substrate. Corresponding fluid-retrieval wells were connected to vacuum at the downstream of the channel block, drawing fluid through the channels and out to a waste container. Thus continuous fluid flow over the substrate in the channel region during coupling steps was achieved.

The complete octamer synthesized at the channel intersections formed by the seventh and eighth coupling steps had the following sequence:

Substrate--(3')CGCAGCCG(5') (SEQ. ID NO:4).

After completion of the synthesis process, cleavage of exocyclic amines was performed by immersion of the reaction region in concentrated ammonium hydroxide. The reaction region was then incubated at 15°C for one hour in a 10 nM solution of the complementary base sequence 5' GCGTCGGC-F (SEQ. ID No:5), where "F" is a fluorescein molecule coupled to the 3' end of the oligonucleotide. The target chain solution was then flushed from the reaction region and replaced with neat 6x SSPE buffer, also at 15°C. Finally, the reaction region was then scanned using a laser fluorescence detection system while immersed in the buffer.

The brightest regions in the resulting image (Fig. 21) correspond to channel intersections where a full octamer was synthesized on the substrate surface. Vertical columns on the image displayed the channel regions where the seventh base was coupled, while horizontal rows display the channel regions where the eighth base was coupled. Brightness in the channel intersection regions indicated hybridization between the fluoresceinated target chain and the complementary chain synthesized and bound to the substrate in these regions. The vertical stripes of the image showed a consistent brightness with regions of significantly greater brightness at the intersection regions. The horizontal stripes did not contain the consistent brightness of the vertical stripes, but did have regions of brightness at the intersections with the vertical stripes.

The consistent brightness along the seventh monomer axis (vertical) indicated partial hybridization of the target chain in areas where seven of the eight complementary bases were coupled to the substrate surface. The lack of brightness along the eighth monomer axis (horizontal) is consistent with the expectation that a chain of six matching bases bound to the substrate surface will not hybridize effectively to an octamer in solution (heptamers with six matching bases followed by a mismatch at the seventh position). The darker background consists of hexamers consisting of the first six monomers coupled to the entire reaction region.

Fig. 22 is a magnified view of the image in Fig. 21. Fig. 22 demonstrates that the separate reaction regions are well resolved.

## VII. Conclusion

The above description is illustrative and not restrictive. Many variations of the invention will become apparent to those of skill in the art upon review of this disclosure. Merely by way of example a variety of substrates, receptors, ligands, and other materials may be used without departing from the scope of the invention. The scope of the invention should, therefore, be determined not with reference to the above description, but instead should be determined with reference to the appended claims along with their full scope of equivalents.



## SEQUENCE LISTING

## (1) GENERAL INFORMATION:

- (i) APPLICANT: Winkler, James L.  
Fodor, Stephen P.A.  
Buchko, Christopher J.  
Aldwin, Lois  
Modlin, Douglas
- (ii) TITLE OF INVENTION: Combinatorial Strategies  
For Polymer Synthesis
- (iii) NUMBER OF SEQUENCES: 5
- (iv) CORRESPONDENCE ADDRESS:
  - (A) ADDRESSEE: Vernon A. Norviel
  - (B) STREET: One Market Plaza, Steuart Tower, Suite 2000
  - (C) CITY: San Francisco
  - (D) STATE: California
  - (E) COUNTRY: USA
  - (F) ZIP: 94105
- (v) COMPUTER READABLE FORM:
  - (A) MEDIUM TYPE: Floppy disk
  - (B) COMPUTER: IBM PC compatible
  - (C) OPERATING SYSTEM: PC-DOS/MS-DOS
  - (D) SOFTWARE: PatentIn Release #1.0, Version #1.25
- (vi) CURRENT APPLICATION DATA:
  - (A) APPLICATION NUMBER: PCT
  - (B) FILING DATE:
  - (C) CLASSIFICATION:
- (vii) PRIOR APPLICATION DATA:
  - (A) DOCUMENT NUMBER: US 07/796,243
  - (B) FILING DATE: 22-NOV-1991
  - (C) CLASSIFICATION:
- (viii) ATTORNEY/AGENT INFORMATION:
  - (A) NAME: Weaver, Jeffrey K.
  - (B) REGISTRATION NUMBER: 31,314
  - (C) REFERENCE/DOCKET NUMBER: 11509-39-1
- (ix) TELECOMMUNICATION INFORMATION:
  - (A) TELEPHONE: 415-326-2600
  - (B) TELEFAX: 415-326-2422

## (2) INFORMATION FOR SEQ ID NO:1:

- (i) SEQUENCE CHARACTERISTICS:  
    (A) LENGTH: 5 amino acids  
    (B) TYPE: amino acid  
    (C) STRANDEDNESS: single  
    (D) TOPOLOGY: linear

(ii) MOLECULE TYPE: peptide

## (xi) SEQUENCE DESCRIPTION: SEQ ID NO:1:

Tyr Gly Gly Phe Leu  
1                    5

## (2) INFORMATION FOR SEQ ID NO:2:

## (i) SEQUENCE CHARACTERISTICS:

- (A) LENGTH: 4 amino acids
- (B) TYPE: amino acid
- (C) STRANDEDNESS: single
- (D) TOPOLOGY: linear

(ii) MOLECULE TYPE: peptide

## (xi) SEQUENCE DESCRIPTION: SEQ ID NO:2:

Tyr Gly Phe Leu

1

## (2) INFORMATION FOR SEQ ID NO:3:

- (i) SEQUENCE CHARACTERISTICS:  
    (A) LENGTH: 4 amino acids  
    (B) TYPE: amino acid  
    (C) STRANDEDNESS: single  
    (D) TOPOLOGY: linear

(ii) MOLECULE TYPE: peptide

(xi) SEQUENCE DESCRIPTION: SEQ ID NO:3:

Gly Gly Phe Leu  
1

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
21

## (2) INFORMATION FOR SEQ ID NO:4:

## (i) SEQUENCE CHARACTERISTICS:

- (A) LENGTH: 8 base pairs
- (B) TYPE: nucleic acid
- (C) STRANDEDNESS: single
- (D) TOPOLOGY: linear

(ii) MOLECULE TYPE: DNA (primer)

(xi) SEQUENCE DESCRIPTION: SEQ ID NO:4:

GCCGACGC

8

## (2) INFORMATION FOR SEQ ID NO:5:

## (i) SEQUENCE CHARACTERISTICS:

- (A) LENGTH: 8 base pairs
- (B) TYPE: nucleic acid
- (C) STRANDEDNESS: single
- (D) TOPOLOGY: linear

## (ii) MOLECULE TYPE: DNA (primer)

## (xi) SEQUENCE DESCRIPTION: SEQ ID NO:5:

GCGTCGGC

8

1 2 3 4 5 6 7 8  
G C G T C G G C  
1 2 3 4 5 6 7 8  
G C G T C G G C

WHAT IS CLAIMED IS:

1. A method of forming polymers having diverse monomer sequences on a single substrate, said substrate comprising a surface with a plurality of selected regions, said method comprising the steps of:

- a) forming a plurality of channels adjacent said surface, said channels at least partially having a wall thereof defined by a portion of said selected regions;
- 10 b) placing selected monomers in said channels to synthesize polymers at said portion of said selected regions, said portion of said selected regions comprising polymers with a sequence of monomers different from polymers in at least one other of said selected regions; and
- 15 c) repeating steps a) and b) with said channels formed along a second portion of said selected regions.

2. The method as recited in claim 1 wherein said step of forming a plurality of channels comprises the step of placing a channel block adjacent said surface, said channel block having a plurality of grooves therein, walls of said grooves and said surface at least partially defining said flow channels.

3. The method as recited in claim 1 wherein the step of placing selected reagents in said channels comprises the steps of:

- removing a protecting group from an active site in at least a first channel;
- flowing a first monomer through said at least a first channel, said first monomer comprising a protecting group thereon, said first monomer binding to said active site in said first channel;
- 30 removing a protecting group from said active site in at least a second channel, at least a portion of said second channel overlapping a portion of said substrate contacted by said first channel; and
- 35 flowing a second monomer through said at least a second channel, said second monomer binding to said active site in said second channel.

4. The method as recited in claim 1 further comprising the step of screening said polymers for binding affinity with a receptor.

5. The method as recited in claim 1 wherein at least 10 different polymers are formed on said surface.

6. The method as recited in claim 1 wherein at least 1,000 different polymers are formed on said surface.

7. The method as recited in claim 1 wherein at least  
5 100,000 different polymers are formed on said surface.

8. The method as recited in claim 1 wherein said  
polymers are selected from the group consisting of oligonucleotides  
and peptides.  
10

9. The method as recited in claim 1 wherein said  
selected regions each have an area of less than about 10,000  
microns<sup>2</sup>.

15 10. The method as recited in claim 3 wherein the steps  
of removing and flowing further comprise the steps of:  
placing a channel block in contact with said surface in a  
first orientation and placing a material comprising a first monomer  
through at least one channel in said channel block;  
20 rotating one of said channel block and said substrate  
relative to the other; and  
placing a channel block in contact with said surface in a  
second orientation and placing a material comprising a second monomer  
through at least one channel in said channel block.  
25

11. The method as recited in claim 1 wherein said steps  
of placing selected reagents in said channels comprises:  
placing a pipet in fluid communication with said channel;  
and  
30 injecting said selected reagents through said channels.

12. The method as recited in claim 11 wherein said step  
of placing a pipet in fluid communication with said channel is a step  
of placing said pipet in contact with an orifice on a side of said  
35 substrate opposite said surface.

13. The method as recited in claim 11 wherein said step  
of placing a pipet in fluid communication with said channel is a step  
of placing a plurality of pipets in communication with a plurality of  
40 said channels and flowing different reagents through at least two of  
said channels.

14. The method as recited in claim 1 preceded by the  
step of forming an array of valves of said surface whereby fluid may  
45 be directed to desired locations on said surface, and selectively



operating said valves and flowing said selected reagents through channels formed thereby.

15        15.    The method as recited in claim 1 preceded by the  
step of irradiating portions of said substrate with light whereby  
photoremovable groups are removed from active groups on said  
substrate.

10        16.    The method as recited in claim 15 wherein said  
selected irradiated portions are in the form of stripes, and wherein  
said step of forming channels comprises forming said channels along a  
path of said stripes, different reagents placed in at least a portion  
of said channels.

15        17.    A method of forming a plurality of peptide  
sequences on a surface of a single substrate comprising the steps of:

- a)    placing said substrate in contact with a channel  
block in a first orientation, said channel block having a plurality  
of channels therein;
- 20        b)    flowing at least a first amino acid through at  
least one of said channels, coupling said first to portions of said  
surface;
- c)    flowing at least a second amino acid through at  
least one of said channels, coupling said second amino acid to  
25        portions of said surface;
- d)    rotating said channel block relative to said  
substrate and placing said substrate in contact with said channel  
block again;
- e)    flowing a third amino acid through at least one of  
30        said channels to form at least first and second peptide sequences on  
said surface; and
- f)    flowing a fourth amino acid through at least one of  
said channels to form at least third and fourth peptide sequences on  
said surface.

35

18.    A kit for forming diverse polymer sequences  
comprising:

- a substrate;
- a channel block, said channel block having a plurality of  
40        grooves therein;
- means for holding said channel block in engagement with  
said substrate;
- means for translating said channel block and said  
substrate relative to the other; and
- 45        means for injecting selected reagents into said grooves.

19. The kit as recited in claim 18 wherein said substrate comprises active site protecting groups.

5 20. The kit as recited in claim 19 further comprising a deprotecting material for removal of said protecting groups.

10 21. The kit as recited in claim 18 wherein said grooves are connected to apertures in said channel block, said apertures extending through a back surface of said substrate.

15 22. The kit as recited in claim 18 further comprising means for irradiating selected portions of said substrate for removal of protecting groups on said substrate, said protecting groups removed from active sites on said substrate upon exposure to light.

20 23. The kit as recited in claim 22 wherein said means for irradiating comprises a light source and a light mask, said light mask comprising regions opaque to said light and regions transmissive to said light.

24. The kit as recited in claim 18 wherein said means for injecting comprises a pipettor.

25. The kit as recited in claim 24 wherein said pipettor comprises a plurality of pipettes, each of which is coupled to a different one of said grooves.

5 26. A system for conducting a plurality of reactions on a single substrate, the system comprising:

at least about 100 reaction regions on the single substrate, each reaction region being capable of conducting a separate reaction;

10 means for delivering one or more reactants to one or more of the reaction regions; and

means for constraining at least some of the reactants from contacting at least some of the reaction regions.

15 27. The system recited in claim 26 wherein the substrate comprises a plurality of passages and the reactions are supported within said passages.

20 28. The system recited in claim 26 wherein the means for delivering the one or more reactants are flow channels of a channel block adjacent the substrate and the means for constraining at least some of the reactants are walls of the flow channel.

25 29. The system recited in claim 26 wherein the means for constraining at least some of the reactants is a hydrophobic layer on the surface of the substrate.

30 30. A substrate comprising  
greater than about 100 reaction regions  
30 having different compounds therein;  
a constraining region surrounding the  
reaction regions, the constraining region being more hydrophobic than  
the reaction regions.

35 31. The substrate recited in claim 30, wherein the constraining region comprises hydrophobic protecting groups.

40 32. The substrate recited in claim 31 wherein the protecting groups are photolabile.

33. The substrate recited in claim 30 wherein the reaction regions define channels.

45 34. The substrate recited in claim 30 wherein the substrate includes greater than about 1000 reaction regions.

35. A method of forming a plurality of polymers having diverse monomer sequences on a substrate, the substrate including a plurality of reaction regions surrounded by a constraining region, the reaction regions being more wettable by one or more monomer solutions than the constraining region, the method comprising
- 5 sequentially placing the one more monomer solutions in a first reaction region to form a first polymer having a first monomer sequence, the monomer solutions being confined to the first reaction region by the constraining region; and
- 10 sequentially placing the one more monomer solutions in a second reaction region to form a second polymer having a second monomer sequence, the monomer solutions being confined to the first reaction region by the constraining region.
- 15 36. The method recited in claim 35 wherein the steps of placing monomer solutions in the first reaction region include moving a pipette with respect to the substrate and depositing at least one monomer solution in the first reaction region.
- 20 37. The method recited in claim 35 further comprising steps of periodically removing monomer solutions from the first and second reaction regions after selected monomers have been coupled to the first and second polymers.
- 25 38. The method recited in claim 35 wherein a first monomer is coupled in the first reaction region and a second monomer is coupled in the second reaction regions before additional monomers are placed and coupled in the first and second reaction regions.
- 30 39. The method recited in claim 35 wherein the monomer solutions are placed in the first and second reaction regions by a dispenser selected from the group consisting of an electrophoretic pump, a pipette, and a charged drop dispenser.
- 35 40. A method of transforming a first heterogeneous array of compounds on a single substrate, the heterogeneous array of compounds having a plurality of reaction regions, the method comprising the following steps:
- 40 activating a first group of reaction regions and a second group of reaction regions;
- delivering a first reactant to the first group of reaction regions but not to the second group of reaction regions;
- 45 allowing the first reactant to react at the first group of reaction regions, to convert the first heterogeneous array

into a second heterogeneous array, wherein the heterogeneous arrays have greater than about 100 distinct reaction regions.

5           41.   The method recited in claim 40 further comprising a step of isolating the first group of reaction regions from the second group of reaction regions.

10           42.   The method recited in claim 41 wherein the first group of reaction regions is isolated by placing a channel block against the substrate.

15           43.   The method recited in claim 40 wherein the first group of reaction regions is isolated from the second group of reaction regions by walls on the substrate.

            44.   The method recited in claim 43 wherein the substrate includes a series of flow through reaction regions separated from one another by walls.

20           45.   The method recited in claim 40 wherein the first group of reaction regions is isolated from the second group of reaction regions by one or more non-wetting regions on the substrate.

25           46.   The method recited in claim 40 wherein the heterogeneous arrays have greater than about 1000 distinct reaction regions.

            47.   The method recited in claim 40 further comprising the following steps:  
30               delivering a second reactant to the second group of reaction regions but not to the first group of reaction regions;  
                allowing the second reactant to react at the second group of reaction regions;  
                activating a third group of reaction regions, the  
35           third group having some reaction regions in common with the first group of reaction regions;  
                delivering a reactant to the third group or reaction regions but not to the second group of reaction regions; and  
                allowing the a reaction to take place in the third  
40           group of reaction regions.

COMBINATORIAL STRATEGIES FOR POLYMER SYNTHESIS

## ABSTRACT OF THE DISCLOSURE

5           A method and device for forming large arrays of polymers  
on a substrate (401). According to a preferred aspect of the  
invention, the substrate is contacted by a channel block (407) having  
channels (409) therein. Selected reagents are delivered through the  
channels, the substrate is rotated by a rotating stage (403), and the  
10 process is repeated to form arrays of polymers on the substrate. The  
method may be combined with light-directed methodologies.

15

20

25

30

35

40

45




FIG. 1






FIG. 2



A	A	B	B
AD	D	AD	D
BD	D	BD	D
A	A	B	B
AD	D	AD	D
BD	D	BD	D
A	A	B	B
AC	C	AC	C
BC	C	BC	C
A	A	B	B
AC	C	AC	C
BC	C	BC	C

FIG. 3







*FIG. 4A*



*FIG. 4B*



*FIG. 4C*




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7A




FIG. 7B

FIG. 8 is a cross-sectional view of a substrate assembly 100, showing a substrate 110 with a top surface 111 and a bottom surface 112. A layer 106 is disposed on the top surface 111, and a layer 108 is disposed on the bottom surface 112. A layer 153 is disposed on the top surface 111, and a layer 123 is disposed on the bottom surface 112. A layer 115 is disposed on the top surface 111, and a layer 117 is disposed on the bottom surface 112. Arrows indicate the direction of light or signal flow.




FIG. 8




FIG. 9




FIG. 10




FIG. 11A




FIG. 11B



FIG. 12 is a perspective view of a device 1000, which includes a base 1001 and a top layer 1002. The base 1001 is a rectangular plate with a grid of rectangular openings 1004. The top layer 1002 is a thin layer that covers the base 1001. The device 1000 is shown in a perspective view, with the base 1001 and top layer 1002 clearly visible. The grid of openings 1004 is composed of many small rectangular cells arranged in a regular pattern.




FIG. 12




FIG. 13A




FIG. 13B




FIG. 14




FIG. 15A




FIG. 15B




FIG. 16A




FIG. 16B




FIG. 17




FIG. 18




FIG. 19






FIG. 20




FIG. 21




FIG. 22

## DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I declare that:

My residence, post office address and citizenship are as stated below next to my name; I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: **COMBINATORIAL STRATEGIES FOR POLYMER SYNTHESIS** the specification of which    is attached hereto or   x   was filed on November 20, 1992 as Application Serial No. 07/ and was amended on            (if applicable). 980,523

I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56. I claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

## Prior Foreign Application(s)

Country	Application No.	Date of Filing	Priority Claimed Under 35 USC 119
			Yes <u>  </u> No <u>  </u>
			Yes <u>  </u> No <u>  </u>

I claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, section 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Application Serial No.	Date of Filing	Status
07/796,243	November 22, 1991	<u>  </u> Patented <u>  x  </u> Pending <u>  </u> Abandoned
07/874,849	April 24, 1992	<u>  </u> Patented <u>  x  </u> Pending <u>  </u> Abandoned






**POWER OF ATTORNEY:** As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connect there therewith.

William M. Smith, Reg. No. 30,223  
 Vernon A. Norviel, Reg. No. 32,483  
 Jeffrey K. Weaver, Reg. No. 31,314  
 Kevin Kaster, Reg. No. 32,704

Send Correspondence to: Jeffrey K. Weaver TOWNSEND and TOWNSEND Stuart Street Tower One Market Plaza, 20th Floor San Francisco, CA 94105	Direct Telephone Calls to:  Jeffrey K. Weaver Reg. No. 31,314 (415) 326-2400
---	--

Full Name of Inventor 1	Last Name WINKLER	First Name James	Middle Name or Initial L.	
Residence & Citizenship	City Palo Alto	State/Foreign Country California	Country of Citizenship USA	
Post Office Address	Post Office Address 2140 Ash Street	City Palo Alto	State/Country California	Zip Code 94306
Full Name of Inventor 2	Last Name FODOR	First Name Stephen	Middle Name or Initial P.A.	
Residence & Citizenship	City Palo Alto	State/Foreign Country California	Country of Citizenship USA	
Post Office Address	Post Office Address 3863 Nathan Way	City Palo Alto	State/Country California	Zip Code 94303
Full Name of Inventor 3	Last Name BUCHKO	First Name Christopher	Middle Name or Initial J.	
Residence & Citizenship	City Ann Arbor	State/Foreign Country Michigan	Country of Citizenship USA	
Post Office Address	Post Office Address 2222 Fuller Road, #405A	City Ann Arbor	State/Country Michigan	Zip Code 48105
Full Name of Inventor 4	Last Name ROSS	First Name Debra	Middle Name or Initial A.	
Residence & Citizenship	City Fremont	State/Foreign Country California	Country of Citizenship USA	
Post Office Address	Post Office Address 3419 Bridgewood Terrace #302	City Fremont	State/Country California	Zip Code 94536
Full Name of Inventor 5	Last Name ALDWIN	First Name Lois	Middle Name or Initial	
Residence & Citizenship	City San Mateo	State/Foreign Country California	Country of Citizenship USA	
Post Office Address	Post Office Address 179 Lakeshore Drive	City San Mateo	State/Country California	Zip Code 94402
Full Name of Inventor 6	Last Name MODLIN	First Name Douglas	Middle Name or Initial N.	
Residence & Citizenship	City Palo Alto	State/Foreign Country California	Country of Citizenship USA	
Post Office Address	Post Office Address 4063 Scripps Avenue	City Palo Alto	State/Country California	Zip Code 94306

I further declare that the contents of this statement are true and correct to the best of my knowledge and belief, and that all statements made on information and belief are believed to be true. I further declare that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Signature of Inventor 1  James L. Winkler	Signature of Inventor 2  Stephen P.A. Fodor	Signature of Inventor 3  Christopher J. Buchko
Date 12/18/92	Date 18 Dec 92	Date
Signature of Inventor 4  Debra A. Ross	Signature of Inventor 5  Lois Aldwin	Signature of Inventor 6  Douglas N. Modlin
Date 12/18/92	Date 12/18/92	Date 12/18/92

## DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I declare that:

My residence, post office address and citizenship are as stated below next to my name; I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: **COMBINATORIAL STRATEGIES FOR POLYMER SYNTHESIS** the specification of which      is attached hereto or x was filed on November 20, 1992 as Application Serial No. 07/980,523 and was amended on              (if applicable).

I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56. I claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

## Prior Foreign Application(s)

Country	Application No.	Date of Filing	Priority Claimed Under 35 USC 119
			Yes <u>    </u> No <u>    </u>
			Yes <u>    </u> No <u>    </u>

I claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, section 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Application Serial No.	Date of Filing	Status
07/796,243	November 22, 1991	<u>    </u> Patented <u>x</u> Pending <u>    </u> Abandoned
07/874,849	April 24, 1992	<u>    </u> Patented <u>x</u> Pending <u>    </u> Abandoned

**POWER OF ATTORNEY:** As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connect there therewith.


William M. Smith, Reg. No. 30,223  
 Vernon A. Norviel, Reg. No. 32,483  
 Jeffrey K. Weaver, Reg. No. 31,314  
 Kevin Kaster, Reg. No. 32,704

Send Correspondence to: Jeffrey K. Weaver TOWNSEND and TOWNSEND Steuart Street Tower One Market Plaza, 20th Floor San Francisco, CA 94105	Direct Telephone Calls to:  Jeffrey K. Weaver Reg. No. 31,314 (415) 326-2400
--	--

Full Name of Inventor 1	Last Name WINKLER	First Name James	Middle Name or Initial L.	
Residence & Citizenship	City Palo Alto	State/Foreign Country California	Country of Citizenship USA	
Post Office Address	Post Office Address 2140 Ash Street	City Palo Alto	State/Country California	Zip Code 94306
Full Name of Inventor 2	Last Name FODOR	First Name Stephen	Middle Name or Initial P.A.	
Residence & Citizenship	City Palo Alto	State/Foreign Country California	Country of Citizenship USA	
Post Office Address	Post Office Address 3863 Nathan Way	City Palo Alto	State/Country California	Zip Code 94303
Full Name of Inventor 3	Last Name BUCHKO	First Name Christopher	Middle Name or Initial J.	
Residence & Citizenship	City Ann Arbor	State/Foreign Country Michigan	Country of Citizenship USA	
Post Office Address	Post Office Address 2222 Fuller Road, #405A	City Ann Arbor	State/Country Michigan	Zip Code 48105
Full Name of Inventor 4	Last Name ROSS	First Name Debra	Middle Name or Initial A.	
Residence & Citizenship	City Fremont	State/Foreign Country California	Country of Citizenship USA	
Post Office Address	Post Office Address 3419 Bridgewood Terrace #302	City Fremont	State/Country California	Zip Code 94536
Full Name of Inventor 5	Last Name ALDWIN	First Name Lois	Middle Name or Initial	
Residence & Citizenship	City San Mateo	State/Foreign Country California	Country of Citizenship USA	
Post Office Address	Post Office Address 179 Lakeshore Drive	City San Mateo	State/Country California	Zip Code 94402
Full Name of Inventor 6	Last Name MODLIN	First Name Douglas	Middle Name or Initial N.	
Residence & Citizenship	City Palo Alto	State/Foreign Country California	Country of Citizenship USA	
Post Office Address	Post Office Address 4063 Scripps Avenue	City Palo Alto	State/Country California	Zip Code 94306



I further declare that the statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Signature of Inventor 1  James L. Winkler	Signature of Inventor 2  Stephen P.A. Fodor	Signature of Inventor 3  Christopher J. Buchko
Date	Date	Date <i>12/7/92</i>
Signature of Inventor 4  Debra A. Ross	Signature of Inventor 5  Lois Aldwin	Signature of Inventor 6  Douglast N. Modlin
Date	Date	Date